TELTONIKA NETWORKS TSW212 Layer2/L3 Managed Ethernet switch

Model: TSW212000000

Manufacturer: TELTONIKA NETWORKS

EAN: 4779051841370

Product Code: 202931

R3,294

The Teltonika TSW212 is an industrial-grade switch designed to meet the demands of modern networks. With its robust data processing capabilities, including a 20 Gbps non-blocking bandwidth and a 14.88 Mpps forwarding rate, it ensures smooth and efficient operation. Security is a priority, with features like RADIUS and TACACS+ authentication providing protection against unauthorized access. The switch's versatile connectivity options, including 8 Gigabit Ethernet ports and 2 SFP slots, make it suitable for a wide range of applications. Its durable, anodized aluminum housing and IP30 protection rating allow it to operate in extreme environmental conditions, from -40 °C to 75 °C. Additionally, the TSW212 supports the Teltonika Remote Management System (RMS), enabling efficient network management and monitoring. Whether deployed in industrial, commercial, or office settings, the TSW212 delivers reliable, secure, and high-speed network connectivity.

Product Description: Teltonika TSW212 - switch - 8 ports - Managed | Device Type: Switch - 8 ports -

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Managed | Subtype: Gigabit Ethernet | Ports: 8 x 10/100/1000 + 2 x SFP | Performance: Non-blocking bandwidth: 20 Gbps Forwarding rate: 14.88 Mpps | Capacity: Packet buffer size: 512 KB | MAC Address Table Size: 8K entries | Jumbo Frame Support: 10000 bytes | Routing Protocol: STP, RSTP, static IPv4 routing, static IPv6 routing | Remote Management Protocol: SNMP 3, SNMP 2, DHCP, RADIUS | Features: Auto-uplink (auto MDI/MDI-X), EtherNet/IP enabled, PROFINET, LLDP support, VLAN support, MRP support, loop protection, DHCP server, DHCP client, port isolation, EEE, port mirroring, DHCPv6 client, PAM, PSK, QoS, DSCP prioritisation, ToS, rate limit, Storm Control, traffic shaping, Teltonika RMS, FOTA, reset button, ground points, anodised aluminium housing | Compliant Standards: IEEE 802.3ab, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z, IEEE 802.1p, IEEE 802.1Q, IEEE 802.1x, IEEE 802.3az | Power: DC 7 - 57 V | Dimensions (WxDxH): 13.2 cm x 12.22 cm x 4.42 cm | Weight: 615 g

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950