TELTONIKA NETWORKS TSW040 8-Port RJ45 PoE+ switch

Model: TSW040000000

Manufacturer: TELTONIKA NETWORKS

EAN: 4779051841448

Product Code: 202933

R1,709

The Teltonika TSW040 is a robust and reliable hub designed for diverse networking needs, offering a capacity with a packet buffer size of 128 KB. It operates effectively in extreme temperatures, ranging from -40°C to 75°C, ensuring adaptability in challenging environments while maintaining a humidity range of 10 - 90% (non-condensing). The switch features eight 10/100 Base-T RJ-45 ports, providing connectivity options for various devices. With power over Ethernet (PoE+) capability of 30 W, this device can support multiple powered devices, enhancing overall efficiency and reducing cable clutter.

Its DIN rail mountable form factor simplifies installation in various settings, making it a component of any network infrastructure. The TSW040 is engineered to meet multiple compliance standards, ensuring reliable performance and security. With non-blocking bandwidth of 20 Gbps and jumbo frame support up to 9216 bytes, this switch offers high-speed data transfer, making it suitable for demanding applications. The anodized aluminum housing provides durability while the status

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

indicators keep users informed about link/activity and power status.

Product Description: Teltonika TSW040 - switch - 8 ports - Managed | Device Type: Switch - 8 ports - Managed | Subtype: Fast Ethernet | Ports: 8 x 10/100 (PoE+) | Power Over Ethernet (PoE): PoE+ | PoE Budget: 240 W | Performance: Non-blocking bandwidth: 20 Gbps | Capacity: Packet buffer size: 128 KB | MAC Address Table Size: 2K entries | Jumbo Frame Support: 9216 bytes | Features: Auto-uplink (auto MDI/MDI-X), anodised aluminium housing | Compliant Standards: IEEE 802.3ab, IEEE 802.3az, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x, IEEE 802.3af, IEEE 802.3at | Power: DC 7 - 57 V | Dimensions (WxDxH): 11.31 cm x 7.46 cm x 4.12 cm | Weight: 280 g

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950