



TELTONIKA NETWORKS TSW100 Industrial PoE+ Ethernet Switch



Model: TSW100010000

Manufacturer: TELTONIKA NETWORKS

EAN: 4779027312828

Product Code: 202946

R2,107

The Teltonika TSW100 is designed to optimize network performance with its non-blocking bandwidth of 10 Gbps, allowing for seamless data transfers across all connected devices. Built with an aluminum housing, it ensures durability and resilience under demanding conditions. The switch is equipped with a robust packet buffer size of 128 KB, supporting a MAC address table size of 2K entries, facilitating improved management of network resources.

Operating efficiently in extreme temperatures ranging from -40°C to 75°C, the TSW100 delivers reliable performance in various environmental conditions. It features Power over Ethernet (PoE) capability, with a budget of 120 W spread across five Gigabit Ethernet ports. Compliant with various IEEE standards, including IEEE 802.3u, IEEE 802.3af, and IEEE 802.3at, this switch is equipped to handle networking needs with flexibility and reliability.

Product Description: Teltonika TSW100 - switch - 5 ports - unmanaged | Device Type: Switch - 5 ports - unmanaged | Subtype: Gigabit Ethernet | Ports: 5 x 10/100/1000 (4 PoE) | Power Over Ethernet

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

(PoE): PoE | PoE Budget: 120 W | Performance: Non-blocking bandwidth: 10 Gbps | Capacity: Packet buffer size: 128 KB | MAC Address Table Size: 2K entries | Jumbo Frame Support: 9216 bytes | Features: Auto-uplink (auto MDI/MDI-X), PROFINET, ground points, aluminium housing | Compliant Standards: IEEE 802.3ab, IEEE 802.3az, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x, IEEE 802.3af, IEEE 802.3at | Power: AC 100-240 V (50/60 Hz) 1.5 A | Dimensions (WxDxH): 11.5 cm x 10.12 cm x 3.22 cm | Weight: 350 g | Localisation: Europe

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950