



TP-Link 48-Port 10/100Mbps Rackmount Network Switch



Model: TL-SF1048

Manufacturer: TP-LINK

EAN: 6935364021702

Product Code: 202971

R3,243

What This Product Does

The TL-SF1048 10/100Mbps Switch is designed to meet the needs of the most demanding workgroup and departmental connectivity requirements. All 48 ports support auto MDI/MDIX, no need to worry about the cable type, simply plug and play. Moreover, with the innovative energy-efficient technology, TL-SF1048 can save up to 50%* of the power consumption and 80% of the packaging material can be recycled, making it an eco-friendly solution for your business network.

TP-LINK Green Technology

This new generation TL-SF1048 10/100Mbps Switch features the latest innovative energy-efficient technologies that can greatly expand your network capacity with much less power. It automatically

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

adjusts power consumption according to the link status and cable length to limit the carbon footprint of your network. It also complies with the EU'S RoHS, prohibiting the use of certain hazardous materials. Besides, 80% of the packaging material can be recycled.

High Performance

Featuring non-blocking switching architecture□ TL-SF1048 forwards and filters packets at full wire-speed for maximum throughput. And IEEE 802.3x flow control for Full Duplex mode and backpressure for Half Duplex mode alleviate the traffic congestion and make TL-SF1048 work reliably.

Easy to Use

The auto features of this Fast Ethernet switch make installation plug and play and hassle-free. No configuring is required. Auto MDI/MDIX eliminates the need for crossover cables. Auto-negotiation on each port senses the link speed of a network device (10, 100Mbps) and intelligently adjusts for compatibility and optimal performance.