



TRENDNET 8-port GREENnet Gigabit PoE Switch 4 PoE 4 Non-PoE



Model: TPE-TG44G

Manufacturer: TRENDNET

EAN: 710931505184

Product Code: 202977

R2,872

TRENDnet's 8-Port Gigabit PoE+ Switch, model TPE-TG44g, reduces equipment and installation costs by delivering data and power over existing Ethernet cables. This unmanaged switch offers four Gigabit PoE+ and four Gigabit non-PoE ports. The PoE+ standard supplies up to 30 W of power per port for devices such as high-power wireless access points, PTZ (Pan Tilt Zoom) Internet cameras, and VoIP telephony systems. Auto sensing technology delivers 30 W to 802.3at PoE+ devices, 15.4 W to 802.3af PoE devices, and only data to non-PoE devices. GREENnet technology reduces energy consumption when the switch is not in use. Boost office efficiency and reduce network congestion with a total switching capacity of 16Gbps. LED indicators display device status for efficient troubleshooting. This switch comes in a sturdy metal case and quickly adds PoE+, PoE, and non-PoE devices to your network.

Product Description: TRENDnet TPE TG44g - switch - 8 ports - TAA Compliant | Device Type: Switch - 8 ports | Subtype: Gigabit Ethernet | Ports: 4 x 10/100/1000 (PoE+) + 4 x 10/100/1000 (PoE+) |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Power Over Ethernet (PoE): PoE+ | Performance: Switching capacity: 16 Gbps Forwarding performance: 1488000 pps | MAC Address Table Size: 1K entries | Jumbo Frame Support: 9KB | Features: Flow control, auto-uplink (auto MDI/MDI-X), store and forward, half duplex mode, full duplex mode, GREENnet technology, Energy Efficient Ethernet, 96KB packet buffer | Compliant Standards: IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3x, IEEE 802.3at, IEEE 802.3az | Power: AC 120/230 V (50/60 Hz) | Dimensions (WxDxH): 14.2 cm x 9.5 cm x 3 cm | Weight: 380 g | TAA Compliant: Yes | Manufacturer Warranty: Limited lifetime warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950