



HPE 5900AF 48G 4XG 2QSFP+ Switch



Model: JG510A

Manufacturer: HEWLETT PACKARD ENTERPRISE

EAN: 887111061720

Product Code: 202980

R163,360

The HPE 5900 Switch Series is a family of high-density, ultra-low-latency, top-of-rack (ToR) switches that is part of the HPE FlexNetwork architecture's HPE FlexFabric solution.

Ideally suited for deployment at the server access layer of large enterprise data centers, the HPE 5900 Switch Series is also powerful enough for deployment at the data center core layer of medium-sized enterprises. With the increase in virtualized applications and server-to-server traffic, customers now require ToR switch innovations that will meet their needs for higher-performance server connectivity, convergence of Ethernet and storage traffic, the capability to handle virtual environments, and ultra low latency all in a single device.

Product Description: HPE 5900AF-48G-4XG-2QSFP+ Switch - switch - 48 ports - Managed - rack-mountable | Device Type: Switch - 48 ports - Managed | Enclosure Type: Rack-mountable 1U | Subtype: Gigabit Ethernet | Ports: 48 x 10/100/1000 + 4 x 10 Gigabit Ethernet / 1 Gigabit Ethernet SFP+ + 2 x 40 Gigabit QSFP+ | Performance: Throughput: 250 Mpps Routing/switching capacity: 336 Gbps | Capacity: IPv4 routing table entries: 16000 IPv6 routing table entries: 8000 | MAC Address Table Size: 128K entries | Jumbo Frame Support: Yes | Routing Protocol: OSPF, BGP-4, RIP-1, RIP-2, BGP, VRRP, OSPFv2, static IP routing, ECMP | Remote Management Protocol: SNMP 1, Telnet, SNMP 3,

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

SNMP 2c, CLI | Features: DHCP support, ARP support, VLAN support, port mirroring, DiffServ support, Broadcast Storm Control, IPv6 support, WRED, RSTP support, VRRP support, MSTP support, ACL support, QoS, DLDP support, STP Root Guard, IRF technology, ISSU | Compliant Standards: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.3ae, IEEE 802.1s, IEEE 802.1ab (LLDP) | Power: AC 120/230 V (50/60 Hz) - power supply not installed | Power Redundancy: Optional | Dimensions (WxDxH): 43.99 cm x 46 cm x 4.37 cm | Weight: 13 kg | Manufacturer Warranty: 1-year warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950