



TRENDNET 16- port Gigabit Web Smart Switch w/ 2 Shared Mini- GBIC Slots (16 PoE, 2SFP)



Model: TPE-1620WS

Manufacturer: TRENDNET

EAN: 710931160093

Product Code: 202984

R10,110

TRENDnet's Gigabit Web Smart PoE+ Switch series offers advanced L2+ features with enhanced traffic management controls to meet the evolving demands of SMB networks. This rack mountable IPv6-ready managed switch comes with an intuitive web-based interface. Advanced managed switch features include LACP to increase bandwidth between switches by grouping ports together, VLANs for segmenting and isolating virtual LAN groups, QoS for traffic prioritization, port bandwidth controls, and SNMP monitoring, making this a powerful solution for any SMB network. Improve voice performance by isolating and prioritizing VoIP traffic from normal data traffic with an easy-to-use voice VLAN feature.

Free up router resources by offloading routing processes to this managed switch by using the L2+

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

IPv4/IPv6 static routing feature to efficiently route traffic at the switch level. The dynamic ARP inspection feature helps protect connected devices from man-in-the-middle attacks by discarding malicious and invalid ARP packets. Take advantage of the available multicast and IGMP/MLD snooping features to optimize IP surveillance system performance, and minimize network traffic. TRENDnet's web smart managed switches also feature SFP slots to support long-distance fiber networking applications.

Installers and integrators can save on equipment costs and reduce installation time with TRENDnet's Web Smart PoE+ Managed Switches by delivering up to 30 W per port of PoE power and data over existing Ethernet cables. With PoE technology, users only need one set of cables to deliver both data and power. With this PoE+ managed switch, network PoE devices, such as high-power wireless access points, PTZ and other advanced IP cameras, VoIP phone systems, IPTV decoders, access controls, and more.

Easily manage and configure TRENDnet's Web Smart PoE+ Managed Switch Series remotely by updating switches to the firmware for access to TRENDnet Hive. TRENDnet Hive is a network cloud manager that reduces management time and cost.

Product Description: TRENDnet TPE 1620WS 16-Port Gigabit Web Smart PoE+ Switch - switch - 16 ports - Managed - rack-mountable - TAA Compliant | Device Type: Switch - 16 ports - Managed | Enclosure Type: Rack-mountable 1U | Subtype: Gigabit Ethernet | Ports: 16 x 10/100/1000 (PoE+) + 2 x shared Gigabit SFP | Power Over Ethernet (PoE): PoE+ | PoE Budget: 185 W | Performance: Switching capacity: 32 Gbps Forwarding performance: 23.8 Mpps | MAC Address Table Size: 16K entries | Jumbo Frame Support: 10KB | Routing Protocol: IGMPv2, IGMP, IGMPv3, static IPv6 routing | Remote Management Protocol: SNMP 1, RMON 1, SNMP 3, SNMP 2c, HTTP, HTTPS | Features: DHCP support, VLAN support, port mirroring, Weighted Round Robin (WRR) queuing, MAC address filtering, IPv6 support, GREENnet technology, Spanning Tree Protocol (STP) support, Rapid Spanning Tree Protocol (RSTP) support, Multiple Spanning Tree Protocol (MSTP) support, DHCP snooping, Access Control List (ACL) support, Jumbo Frames support, reset button, bandwidth control, LLDP support, Link Aggregation Control Protocol (LACP), Management Information Base (MIB), Dynamic VLAN Support (GVRP), Network Access Control (NAC), Strict Priority Queuing (SPQ), Neighbor Discovery Protocol (NDP), Class of Service (CoS), tagged VLAN, Loopback, Denial of Service (DoS), Duplicated Address Detection | Compliant Standards: IEEE 802.3, IEEE 802.3u, IEEE 802.3z, IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3af, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.1s, IEEE 802.1ab (LLDP), IEEE 802.3at, IEEE 802.3az | Power: AC 120/230 V (50/60 Hz) | Dimensions (WxDxH): 44 cm x 25.1 cm x 4.445 cm | Weight: 3.6 kg | System

Requirements: Microsoft Windows Vista (32/64 bits), Microsoft Windows 7 (32/64 bits), Microsoft

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Windows XP (32/64 bits), Microsoft Windows Server 2008 (32/64-bits), Microsoft Windows Server 2003 (32/64-bits), Windows 8 (32/64 bits) | TAA Compliant: Yes | Manufacturer Warranty: Limited lifetime warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950