



HPE Aruba 5412R zl2 Switch



Model: J9822A

Manufacturer: HEWLETT PACKARD ENTERPRISE

EAN: 888182309032

Product Code: 202988

R141,341

The HPE 5400R zl2 Switch series is the next-generation modular switch designed for enterprise edge and SMB and branch office core deployments. With enterprise-class resiliency and unprecedented flexibility, scalability and ease of use, the 5400R supports demanding network features such as hitless failover, power supply redundancy, QoS and security with full L3 features.

Robust virtualization with HPE AllianceOne solutions and flexible connectivity including 10 Gigabit Ethernet and full PoE+, the 5400R requires no add-on software licensing and is SDN ready with OpenFlow support.

Product Description: HPE Aruba 5412R zl2 - switch - Managed - rack-mountable | Device Type: Switch - Managed | Enclosure Type: Rack-mountable 7U | Subtype: Gigabit Ethernet | Performance:

Throughput: 785.7 Mpps Routing/switching capacity: 1 Tbps | Capacity: IPv4 routing table entries: 10000 IPv6 routing table entries: 5000 | MAC Address Table Size: 64K entries | Routing Protocol: OSPF, RIP-1, RIP-2, BGP, IGMP, VRRP, OSPFv2, PIM-SM, PIM-DM, IGMPv3, OSPFv3, static IPv6 routing, MLDv2, MLD, CIDR | Remote Management Protocol: SNMP 1, RMON 1, RMON 2, SNMP, Telnet, SNMP 3, SNMP 2c, HTTP, TFTP, SMON, SSH, CLI, XRMON | Features: Flow control, DHCP support, BOOTP support, ARP support, trunking, VLAN support, auto-uplink (auto MDI/MDI-X), DiffServ support, IPv6

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

support, half duplex mode, full duplex mode, SNTP support, RSTP support, MSTP support, tunnelling, ACL support, QoS, MLD snooping, NSR, bandwidth control, STP Root Guard, UDLD, Rapid PVST+, IPv4 support, DHCP relay, Port Security, fan tray, DHCP client, Energy Efficient Ethernet, MIB, dynamic ARP protection, DHCP protection, dual firmware images, CoS, sFlow v5, GVRP, ToS | Compliant Standards: IEEE 802.3, IEEE 802.3u, IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3af, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.1s, IEEE 802.1ad, IEEE 802.1v, IEEE 802.1ab (LLDP), IEEE 802.3at, IEEE 802.3az, IEEE 802.1AX | Power: AC 120/230 V (50/60 Hz) - power supply not installed | Power Redundancy: Optional | Dimensions (WxDxH): 44.45 cm x 45.09 cm x 30.73 cm | Weight: 17.28 kg | Manufacturer Warranty: Limited lifetime warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950