HPE 5700 40XG 2QSFP+ Switch

Model: JG896A

Manufacturer: HEWLETT PACKARD ENTERPRISE

EAN: 888182312902

Product Code: 202992

R222,269

The HPE FlexFabric 5700 Switch Series provides an open door for expanding your enterprise network by adding capacity with local switching and L2/L3 support. Take advantage of IRF enhancements for spine/leaf configurations, to simplify network management and expand server connectivity. Resilience and ease of management come hand-in-hand with the FlexFabric 5700. IRF reduces management complexities. You can rely on the FlexFabric 5700 to lower TCO with lower cost than competing devices.

Product Description: HPE FlexFabric 5700-40XG-2QSFP+ - switch - 40 ports - Managed - rack-mountable | Device Type: Switch - 40 ports - L3 - Managed | Enclosure Type: Rack-mountable 1U | Subtype: 10 Gigabit Ethernet | Ports: 40 x 1 Gigabit / 10 Gigabit SFP+ + 2 x 40 Gigabit QSFP+ (uplink) | Performance: Throughput: 714.2 Mpps Routing/switching capacity: 960 Gbps | Capacity: IPv4 routing table entries: 128 IPv6 routing table entries: 128 Virtual interfaces (VLANs): 4096 | MAC Address Table Size: 128K entries | Jumbo Frame Support: Yes | Routing Protocol: RIP-1, RIP-2, IGMPv2, IGMP, IGMPv3, static IPv4 routing, static IPv6 routing | Remote Management Protocol: SNMP 1, Telnet, SNMP 3, SNMP 2c, TFTP, SSH, SSH-2, CLI | Features: Flow control, DHCP support, ARP support, IGMP snooping, port mirroring, WRR queuing, SNTP support, WFQ, WRED, sFlow, PIM snooping, MSTP support, DCBX support, priority-based flow control, ACL support, QoS, Jumbo Frames support, MLD snooping, DLDP support, ECMP, LLDP support, DCB, MIB, NTP time synchronisation,

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

CoS, SP, IRF technology, FCoE support | Compliant Standards: IEEE 802.3, IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.3ae, IEEE 802.1s, IEEE 802.1ad, IEEE 802.3ah, IEEE 802.1ag, IEEE 802.1ab (LLDP), IEEE 802.1Qbb, IEEE 802.3ag | Power Redundancy: Optional | Dimensions (WxDxH): 43.99 cm x 46 cm x 4.37 cm | System Requirements: Comware v7 | Manufacturer Warranty: 1-year warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950