



HPE 5130 24G 4SFP+ EI Switch HPE 5130 24G 4SFP+ EI Switch EU en



Model: JG932A#ABB

Manufacturer: HEWLETT PACKARD ENTERPRISE

EAN: 888182606612

Product Code: 202995

R73,442

The HPE 5130 EI Switch Series is comprised of Gigabit Ethernet switches that support static and RIP Layer 3 routing, diversified services, and IPv6 forwarding, as well as provide four 10-Gigabit Ethernet (10GbE) extended interfaces. Unique Intelligent Resilient Framework (IRF) technology creates a virtual fabric by managing several switches as one logical device, which increases network resilience, performance, and availability, while reducing operational complexity. These switches provide Gigabit Ethernet access and can be used at the edge of a network or to connect server clusters in data centers. High availability, simplified management, and comprehensive security control policies are among the key features that distinguish this series.

Product Description: HPE 5130-24G-4SFP+ EI - switch - 24 ports - Managed - rack-mountable | Device Type: Switch - 24 ports - L3 - Managed | Enclosure Type: Rack-mountable 1U | Subtype: Gigabit Ethernet | Ports: 24 x 10/100/1000 + 4 x 10 Gigabit Ethernet / 1 Gigabit Ethernet SFP+ |

Performance: Throughput: 96 Mpps Routing/switching capacity: 128 Gbps | Capacity: IPv4 routing

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

table entries: 512 IPv6 routing table entries: 256 | MAC Address Table Size: 16K entries | Jumbo Frame Support: 9216 bytes | Routing Protocol: Static IPv4 routing, static IPv6 routing | Remote Management Protocol: SNMP 1, RMON 1, RMON 2, RMON 3, RMON 9, SNMP 3, SNMP 2c, HTTP, HTTPS, CLI | Features: DHCP support, ARP support, VLAN support, auto-uplink (auto MDI/MDI-X), IGMP snooping, WRR queuing, IPv6 support, sFlow, RSTP support, MSTP support, ACL support, QoS, Jumbo Frames support, MLD snooping, PVST+, DLDP support, RRPP, EAD, STP Root Guard, LLDP support, DHCP relay, Port Security, dynamic ARP protection, DHCP protection, SPQ, port isolation, tagged VLAN, GARP, IRF technology | Compliant Standards: IEEE 802.3, IEEE 802.3u, IEEE 802.3i, IEEE 802.3z, IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.3ae, IEEE 802.1s, IEEE 802.1ad, IEEE 802.3ah, IEEE 802.1ab (LLDP) | Power: AC 120/230 V | Dimensions (WxDxH): 44 cm x 16 cm x 4.36 cm | Weight: 5 kg | Localisation: English / Europe | Manufacturer Warranty: Limited lifetime warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950