



HPE Aruba 5406R 44GT PoE+/4SFP+ v3 zl2 Swch

Model: JL003A

Manufacturer: HEWLETT PACKARD ENTERPRISE

EAN: 888182604373

Product Code: 203000

R278,904

The HPE 5400R zl2 Switch Series is an industry leading mobile campus access solution with HPE smart rate multi-Gigabit ports for high speed connectivity and bandwidth for next wave 802.11ac devices. It brings enterprise-class resiliency and innovative flexibility and scalability to converged campus networks.

Robust virtualization with HPE AllianceOne solutions, hitless failover, QoS and security with full L3 features and flexible connectivity including 40 Gigabit Ethernet ports and full PoE+, the 5400R requires no add-on software licensing and is SDN ready with OpenFlow support.

Product Description: HPE Aruba 5406R 44GT PoE+ / 4SFP+ (No PSU) v3 zl2 - switch - 44 ports - Managed - rack-mountable | Device Type: Switch - 44 ports - Managed | Enclosure Type: Rack-mountable 4U | Subtype: Gigabit Ethernet | Ports: 44 x 10/100/1000 (PoE+) + 4 x 1 Gigabit / 10 Gigabit SFP+ | Power Over Ethernet (PoE): PoE+ | Performance: Routing/switching capacity: 960 Gbps Throughput: up to 571.4 Mpps Switching fabric bandwidth: 1015 Gbps | Capacity: IPv4 routing table entries: 10000 IPv6 routing table entries: 5000 | MAC Address Table Size: 64K entries | Jumbo

Frame Support: Yes | Routing Protocol: RIP-1, RIP-2, BGP, IGMP, VRRP, OSPFv2, PIM-SM, static IP

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

routing, PIM-DM, IGMPv3, OSPFv3, static IPv6 routing, MLDv2, MLD | Remote Management Protocol: SNMP 1, RMON 1, RMON 2, RMON 3, RMON 9, Telnet, SNMP 3, SNMP 2c, HTTP, TFTP, SMON, CLI, XRMON | Features: Flow control, routing, DHCP support, BOOTP support, ARP support, trunking, VLAN support, auto-uplink (auto MDI/MDI-X), IGMP snooping, DiffServ support, IPv6 support, half duplex mode, full duplex mode, STP support, RSTP support, MSTP support, tunnelling, ACL support, QoS, MLD snooping, NSR, bandwidth control, STP Root Guard, UDLD, Rapid PVST+, IPv4 support, DHCP relay, Port Security, fan tray, DHCP client, Energy Efficient Ethernet, MIB, dynamic ARP protection, DHCP protection, dual firmware images, CoS, sFlow v5, GVRP, ToS, MACsec support | Compliant Standards: IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3af, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.1s, IEEE 802.1ad, IEEE 802.1v, IEEE 802.1ab (LLDP), IEEE 802.3at, IEEE 802.3az, IEEE 802.1AX | Dimensions (WxDxH): 44.45 cm x 45.09 cm x 17.53 cm | Weight: 12.75 kg | Manufacturer Warranty: Limited lifetime warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950