



HPE OfficeConnect 1950 24G 2SFP+ 2XGT Switch HPE OfficeConnect 1950 24G 2SFP+ 2XGT Switch Europe - english localization

Model: JG960A#ABB

Manufacturer: HEWLETT PACKARD ENTERPRISE

EAN: 888182694800

Product Code: 203002

R28,832

HPE Smart switches offer a great class of switching for costs conscious customers that need performance and basic to advanced network control. The HPE range of products offers customers a choice from low cost unmanaged to advanced configurable smart managed switches. Whatever your Network Security, performance reliability and management needs HPE has a selection of products to match them.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

With this special offer on the HPE Switch and HPE Gigabit SX transceiver you have Flexibility in your network design for Switch to Switch, Switch to server and Storage connectivity. HPE original transceivers provide peace of mind with guaranteed compatibility.

Product Description: HPE 1950-24G-2SFP+-2XGT - switch - 24 ports - Managed - rack-mountable | Device Type: Switch - 24 ports - L3 - Managed - stackable | Enclosure Type: Rack-mountable 1U | Subtype: Gigabit Ethernet | Ports: 24 x 10/100/1000 + 2 x Gigabit SFP / 10 Gigabit SFP+ + 2 x 10Gb Ethernet | Performance: Throughput (64-byte packet size): up to 95.2 Mpps Routing/switching capacity: 128 Gbps | Capacity: Static routes: 32 Virtual interfaces (VLANs): 8 IPv4 routing table entries: 32 IPv6 routing table entries: 32 | MAC Address Table Size: 16384 entries | Jumbo Frame Support: 10KB | Routing Protocol: IGMP, VRRP, static IPv4 routing, static IPv6 routing, ECMP | Remote Management Protocol: SNMP 1, RMON 2, RMON, SNMP 3, SNMP 2c, HTTP, HTTPS, CLI | Features: Auto-uplink (auto MDI/MDI-X), IGMP snooping, port mirroring, STP support, ACL support, QoS, STP Root Guard, LACP, DHCP client, packet storm protection, CoS | Compliant Standards: IEEE 802.3, IEEE 802.3i, IEEE 802.3z, IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.1s, IEEE 802.1ab (LLDP), IEEE 802.3at | Power: AC 120/230 V (50/60 Hz) | Dimensions (WxDxH): 43.6 cm x 16 cm x 4.4 cm | Weight: 3 kg | Localisation: English / Europe | Manufacturer Warranty: Limited lifetime warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950