



HPE OfficeConnect 1950 48G 2SFP+ 2XGT Switch HPE OfficeConnect 1950 48G 2SFP+ 2XGT Switch Europe - english localization

Model: JG961A#ABB

Manufacturer: HEWLETT PACKARD ENTERPRISE

EAN: 888182695005

Product Code: 203003

R48,543

HPE 1950 Switches are smart web-managed Gigabit switches with 10G uplinks, for small business customers needing advanced high-performance connections. The series has two standard models and two PoE+ models, 24 and 48 Gigabit ports, each with two 10GBASE-T ports and two 10G SFP+ high-bandwidth ports.

The switches deliver true-stacking, allowing up to four devices to be logically administered as a

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

single entity. They support Layer 3 static routing on IPv4 and IPv6.

Product Description: HPE 1950-48G-2SFP+-2XGT - switch - 48 ports - Managed - rack-mountable |
Device Type: Switch - 48 ports - L3 - Managed - stackable | Enclosure Type: Rack-mountable 1U |
Subtype: Gigabit Ethernet | Ports: 48 x 10/100/1000 + 2 x Gigabit SFP / 10 Gigabit SFP+ + 2 x 10Gb
Ethernet | Performance: Throughput (64-byte packet size): up to 130.9 Mpps Routing/switching
capacity: 176 Gbps | Capacity: Static routes: 32 Virtual interfaces (VLANs): 8 IPv4 routing table
entries: 32 IPv6 routing table entries: 32 | MAC Address Table Size: 16384 entries | Jumbo Frame
Support: 10KB | Routing Protocol: IGMP, VRRP, static IPv4 routing, static IPv6 routing, ECMP | Remote
Management Protocol: SNMP 1, RMON 2, RMON, SNMP 3, SNMP 2c, HTTP, HTTPS, CLI | Features:
Auto-uplink (auto MDI/MDI-X), IGMP snooping, port mirroring, STP support, ACL support, QoS, STP
Root Guard, LACP, DHCP client, packet storm protection, CoS | Compliant Standards: IEEE 802.3,
IEEE 802.3u, IEEE 802.1ab (LLDP) | Power: AC 120/230 V (50/60 Hz) | Dimensions (WxDxH): 44 cm x
27 cm x 4.4 cm | Weight: 5 kg | Localisation: English / Europe | Manufacturer Warranty: Limited
lifetime warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950