



HPE OfficeConnect 1950 48G 2SFP+ 2XGT PoE+ Switch HPE OfficeConnect 1950 48G 2SFP+ 2XGT PoE+ Switch Europe - english localization

Model: JG963A#ABB

Manufacturer: HEWLETT PACKARD ENTERPRISE

EAN: 888182695401

Product Code: 203005

R66,351

HPE 1950 Switch Series is part of the HPE OfficeConnect portfolio of small business network solutions designed for simplicity, reliability, and affordability. The HPE 1950 Switch Series is a smart-managed switch with 10G uplinks for faster server and storage connections to servers and storage to reduce

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

bottlenecks and help organizations keep pace with today's bandwidth-demanding applications. The 1950 Switch Series features an intuitive Web-managed interface for simple customization of network operation. With four-high stacking, organizations can manage up to four 1950 devices as a single unit, saving time and reducing the potential for human error. The HPE 1950 Switch Series provides a great value and includes features to satisfy the 10G connectivity needs of even the most advanced small business network.

Product Description: HPE 1950-48G-2SFP+-2XGT-PoE+ - switch - 48 ports - Managed - rack-mountable | Device Type: Switch - 48 ports - L3 - Managed - stackable | Enclosure Type: Rack-mountable 1U | Subtype: Gigabit Ethernet | Ports: 48 x 10/100/1000 (PoE+) + 2 x 10 Gigabit Ethernet / 1 Gigabit Ethernet SFP+ + 2 x 10Gb Ethernet | Power Over Ethernet (PoE): PoE+ | PoE Budget: 370 W | Performance: Throughput (64-byte packet size): 130.9 Mpps Routing/switching capacity: 176 Gbps | Capacity: IPv4 routing table entries: 32 IPv6 routing table entries: 32 | MAC Address Table Size: 16384 entries | Jumbo Frame Support: Yes | Routing Protocol: IGMP, static IPv4 routing, static IPv6 routing | Remote Management Protocol: SNMP 1, RMON 2, SNMP 3, SNMP 2c, HTTP, HTTPS | Features: ARP support, port mirroring, half duplex mode, full duplex mode, STP support, VRRP support, ACL support, QoS, MLD snooping, ECMP, STP Root Guard, LLDP support, LACP, packet storm protection, CoS | Compliant Standards: IEEE 802.3, IEEE 802.3u, IEEE 802.3i, IEEE 802.3z, IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3af, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.1s, IEEE 802.1ab (LLDP), IEEE 802.3at | Power: AC 120/230 V (50/60 Hz) | Dimensions (WxDxH): 44 cm x 42 cm x 4.4 cm | Weight: 7 kg | Localisation: English / Europe | Manufacturer Warranty: Limited lifetime warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950