



HPE Aruba 3810M 48G PoE+ 1-slot Swch



Model: JL074A

Manufacturer: HEWLETT PACKARD ENTERPRISE

EAN: 888793596609

Product Code: 203016

R165,127

The Aruba 3810 Switch Series is a mobile campus access solution for enterprises, SMBs, and branch office networks. With HPE Smart Rate multi-gigabit ports for high-speed IEEE 802.11ac devices, the Aruba 3810 will prepare your network for tomorrow. Dual, redundant, hot-swappable power supplies and innovative backplane stacking technology delivers resiliency and scalability in a convenient 1U form factor. With support for OpenFlow, the Aruba 3810 is ready to take advantage of SDN applications such as HPE Network Visualizer, HPE Network Optimizer, and HPE Network Protector applications.

Product Description: HPE Aruba 3810M 48G PoE+ 1-slot Switch - switch - 48 ports - Managed - rack-mountable | Device Type: Switch - 48 ports - L3 - Managed - stackable | Enclosure Type: Rack-mountable 1U | Subtype: Gigabit Ethernet | Ports: 48 x 10/100/1000 (PoE+) | Power Over Ethernet (PoE): PoE+ | Performance: Latency (1000Base-T): 2.8 µs Latency (10 Gbps): 1.8 µs Latency (40 Gbps): 1.5 µs Throughput (64-byte packet size): up to 190.5 Mpps Routing/switching capacity: 320 Gbps Switching fabric bandwidth: 338 Gbps | Capacity: IPv4 routing table entries: 10000 IPv6 routing table entries: 5000 | MAC Address Table Size: 64K entries | Jumbo Frame Support: Yes | Routing

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Protocol: OSPF, RIP, RIP-1, RIP-2, BGP, VRRP, OSPFv2, OSPFv3, static IPv4 routing, static IPv6 routing, RIPng, MLD, Bidirectional Forwarding Detection (BFD) | Remote Management Protocol: SNMP 1, RMON 1, RMON 2, RMON 3, RMON 9, RMON, Telnet, SNMP 3, SNMP 2c, HTTP, SSH, SSH-2, CLI, XRMON | Features: ARP support, STP support, PVST, ACL support, QoS, DLDP support, UDLD, MIB, GVRP, MVRP, CoS, sFlow v5, ToS, OpenFlow support, ICMP | Compliant Standards: IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3af, IEEE 802.3ad (LACP), IEEE 802.1x, IEEE 802.1s, IEEE 802.1v, IEEE 802.11n, IEEE 802.1ab (LLDP), IEEE 802.3at | Environmental Standards: ENERGY STAR Qualified | Dimensions (WxDxH): 44.25 cm x 43.13 cm x 4.39 cm | Weight: 6.18 kg | Manufacturer Warranty: Limited lifetime warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950