



HPE Aruba 3810M 16SFP+ 2-slot Swch



Model: JL075A

Manufacturer: HEWLETT PACKARD ENTERPRISE

EAN: 888793596616

Product Code: 203017

R267,513

The Aruba 3810 switch series provides performance and resiliency for the digital workplace campus network. Based on a powerful ProVision ASIC and ready for high-speed APs with HPE Smart Rate multi-gigabit Ethernet, the Aruba 3810 delivers a better application experience with low latency, virtualization with resilient stacking technology, and line rate 40 GbE for plenty of back haul capacity.

Product Description: HPE Aruba 3810M 16SFP+ 2-slot Switch - switch - 16 ports - Managed - rack-mountable | Device Type: Switch - 16 ports - L3 - Managed - stackable | Enclosure Type: Rack-mountable 1U | Subtype: 10 Gigabit Ethernet | Ports: 16 x 10 Gigabit SFP+ | Performance: Latency (1 Gbps): 2.8 µs Latency (10 Gbps): 1.8 µs Latency (40 Gbps): 1.5 µs Throughput (64-byte packet size): up to 285.7 Mpps Routing/switching capacity: 480 Gbps Switching fabric speed: 508 Gbps | Capacity: IPv4 routing table entries: 10000 IPv6 forwarding table entries: 5000 | MAC Address Table Size: 64K entries | Jumbo Frame Support: Yes | Routing Protocol: OSPF, BGP-4, RIP-1, RIP-2, BGP, VRRP, OSPFv2, IGMPv3, OSPFv3, static IPv4 routing, static IPv6 routing, RIPng, MLD, Bidirectional Forwarding Detection (BFD), CIDR | Remote Management Protocol: SNMP 1, RMON 1, RMON 2, RMON 3, RMON 9, Telnet, SNMP 3, SNMP 2c, CLI, XRMON, SSH 6 | Features: Flow control, DHCP support,

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

BOOTP support, VLAN support, auto-uplink (auto MDI/MDI-X), Syslog support, IPv6 support, half duplex mode, full duplex mode, sFlow, VRRP support, MSTP support, QoS, PVST+, STP Root Guard, UDLD, LACP, dynamic ARP protection, DHCP protection, GVRP, Zero Touch Auto Provisioning, MVRP, Ingress Layer 2 MAC ACLs, CoS, MACsec support, DNS client, layer 4 prioritisation:, 13.5MB packet buffer | Compliant Standards: IEEE 802.3, IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.1s, IEEE 802.1ad, IEEE 802.1v, IEEE 802.1AX | Power Redundancy: Yes | Dimensions (WxDxH): 44.25 cm x 43.13 cm x 4.39 cm | Weight: 6.02 kg | Manufacturer Warranty: Limited lifetime warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950