CSSi SA - "Securing Tomorrow, Today"
Waterfall Office Park, 28 Augrabies Rd Vorna Valley, Midrand, 1685
Generated: 2026-10-30 19:15

HPE 5510 24G 4SFP+ HI Swch

Model: JH145A

Manufacturer: HEWLETT PACKARD ENTERPRISE

EAN: 888793785690

Product Code: 203019

R109,128

The HPE 5510-24G-4SFP HI is designed for seamless network connectivity and efficient data management. This Gigabit Ethernet switch offers 24 ports with a routing capacity of 288 Gbps, ensuring high performance and reliability for demanding applications. With support for various routing protocols such as OSPF, BGP, and MPLS, it enables robust and flexible network configurations. The inclusion of a rack mounting kit makes installation straightforward and convenient, allowing for efficient use of space in server rooms.

Designed to operate within a wide temperature range from 0°C to 50°C and equipped to handle humidity levels of 5-95% non-condensing, the HPE 5510-24G-4SFP HI is reliable in diverse environments. It also boasts features such as layer 3 switching, jumbo frame support, and Quality of Service (QoS), providing enhanced traffic management and improved network performance. This switch is manageable via SNMP, CLI, and other remote management protocols, offering users the control they need for a secure and efficient networking setup.

Product Description: HPE 5510-24G-4SFP HI Switch with 1 Interface Slot - switch - 24 ports - Managed - rack-mountable | Device Type: Switch - 24 ports - Managed - stackable | Enclosure Type: Rack-mountable 1U | Subtype: Gigabit Ethernet | Ports: 24 x 10/100/1000 + 4 x Gigabit SFP + 4 x 10 Gigabit SFP+ | Performance: Routing/switching capacity: 288 Gbps Throughput: 214 Mpps | Jumbo Frame Support: Yes | Routing Protocol: OSPF, RIP, IS-IS, BGP, VRRP, PIM-SM, static IP routing, PIM-DM,

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

OSPFv3, PIM-SSM, ECMP, RIPng, IS-ISv6, MPLS, Bidirectional Forwarding Detection (BFD) | Remote Management Protocol: SNMP 1, RMON, Telnet, SNMP 3, SNMP 2c, CLI | Features: Layer 3 switching, DHCP support, ARP support, MPLS support, auto-uplink (auto MDI/MDI-X), IPv6 support, STP support, RSTP support, VRRP support, MSTP support, QoS, RRPP, ECMP, BFD, STP Root Guard, IPv4 support | Compliant Standards: IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3x, IEEE 802.1x, IEEE 802.1ad, IEEE 802.1ab (LLDP) | Dimensions (WxDxH): 44 cm x 36 cm x 4.37 cm | Weight: 7.5 kg | Manufacturer Warranty: Limited lifetime warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950