HPE 5510 48G 4SFP+ HI Swch

Model: JH146A

Manufacturer: HEWLETT PACKARD ENTERPRISE

EAN: 888793785706

Product Code: 203020

R170,490

The HPE 5510-48G-4SFP HI is a versatile switch designed for rack-mounted applications, providing connectivity options with 48 1000Base-T ports. Offering layer 3 switching capabilities, this device supports various routing protocols including OSPF, BGP, and RIP among others, enhancing network performance and reliability. With a throughput of 250 Mpps and a switching capacity of 336 Gbps, it effectively supports medium to large-sized networks, ensuring smooth data transmission.
Equipped with 512 MB of flash memory and 2 GB of SDRAM, the switch features an expansion slot for future upgrades. Its stackable design allows for easy scaling, while functionalities like Quality of Service (QoS) and Spanning Tree Protocol (STP) support help maintain efficient, reliable network management. Additionally, the unit supports remote management through SNMP and CLI, simplifying monitoring and administration tasks.
Product Description: HPE 5510-48G-4SFP HI Switch with 1 Interface Slot - switch - 48 ports - Managed - rack-mountable | Device Type: Switch - 48 ports - Managed - stackable | Enclosure Type: Rack-mountable 1U | Subtype: Gigabit Ethernet | Ports: 48 x 10/100/1000 + 4 x Gigabit SFP + 4 x 10 Gigabit SFP+ | Performance: Routing/switching capacity: 336 Gbps Throughput: 250 Mpps | Jumbo Frame Support: Yes | Routing Protocol: OSPF, RIP, IS-IS, BGP, VRRP, PIM-SM, static IP routing, PIM-DM, OSPFv3, PIM-SSM, ECMP, RIPng, IS-ISv6, MPLS, Bidirectional Forwarding Detection (BFD) | Remote Management Protocol: SNMP 1, RMON, Telnet, SNMP 3, SNMP 2c, CLI | Features: Layer 3 switching,

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

DHCP support, ARP support, MPLS support, auto-uplink (auto MDI/MDI-X), IPv6 support, STP support, RSTP support, VRRP support, MSTP support, QoS, RRPP, ECMP, BFD, STP Root Guard, IPv4 support | Compliant Standards: IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3x, IEEE 802.1x, IEEE 802.1ad, IEEE 802.1ab (LLDP) | Dimensions (WxDxH): 44 cm x 36 cm x 4.37 cm | Weight: 7.5 kg | Manufacturer Warranty: Limited lifetime warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950