HPE 5130 48G 4SFP+ 1-slot HI Switch

Model: JH324A

Manufacturer: HEWLETT PACKARD ENTERPRISE

EAN: 889296940395

Product Code: 203023

R158,480

The HPE FlexNetwork 5130 HI Switch Series delivers scalability and resiliency at the access layer of medium and large enterprise campus networks. This FlexNetwork switch supports enterprise class QoS and security, HPE Intelligent Resilient Framework (IRF) stacking, static Layer 3 routing and RIP, dual redundant power supplies, fixed and modular 10GbE uplinks ports, PoE+, ACLs, IPv6 and delivers energy savings with Energy Efficient Ethernet.
Product Description: HPE 5130-48G-4SFP+ 1-slot HI - switch - 48 ports - Managed - rack-mountable | Device Type: Switch - 48 ports - L3 - Managed - stackable | Enclosure Type: Rack-mountable 1U | Subtype: Gigabit Ethernet | Ports: 48 x 10/100/1000 + 4 x 10 Gigabit SFP+ | Performance: Throughput: up to 190.5 Mpps Routing/switching capacity: 256 Gbps | Capacity: Simultaneous VLANs: 4094 IPv4 routing table entries: 32768 IPv6 routing table entries: 16384 | Jumbo Frame Support: 9KB | Routing Protocol: RIP-1, RIP-2, IGMPv2, IGMP, PIM-SM, IGMPv3, MSDP, MLD | Remote Management Protocol: SNMP 1, RMON 1, RMON 2, RMON 3, RMON 9, Telnet, SNMP 3, SNMP 2c, HTTPS, TFTP, SSH-2, CLI, SCP | Features: Flow control, DHCP support, ARP support, VLAN support, auto-uplink (auto MDI/MDI-X), Syslog support, WRR queuing, IPv6 support, sFlow, STP support, RSTP support, VRRP support, MSTP support, PAgP support, ACL support, QoS, CAR, DHCP server, DLDP

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

support, ECMP, STP Root Guard, IPv4 support, LLDP support, Smart Link Pass-Through, dynamic ARP protection, DHCP protection, port isolation, non blocking ports, SP, GARP, IRF technology, OpenFlow support, IP source guard | Compliant Standards: IEEE 802.3, IEEE 802.3u, IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3x, IEEE 802.1w, IEEE 802.1x, IEEE 802.3ae, IEEE 802.1s, IEEE 802.1ad, IEEE 802.3ah, IEEE 802.1ab (LLDP), IEEE 802.1ak, IEEE 802.3az | Power: AC 120/230 V (50/60 Hz) - power supply not installed | Power Redundancy: Optional | Dimensions (WxDxH): 44 cm x 36 cm x 4.37 cm | Weight: 7.5 kg | Manufacturer Warranty: Limited lifetime warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950