



HPE 5130 24G PoE+ 4SFP+ 1- slot HI Switch



Model: JH325A

Manufacturer: HEWLETT PACKARD ENTERPRISE

EAN: 889296940425

Product Code: 203024

R115,805

The HPE FlexNetwork 5130 HI Switch Series comprises Gigabit Ethernet switches that support static and RIP Layer 3 routing, diversified services, and IPv6 forwarding, as well as provide four 10-Gigabit Ethernet (10GbE) interfaces.

Unique Intelligent Resilient Fabric (IRF) technology creates a virtual fabric by managing several switches as one logical device, which increases network resilience, performance, and availability, while reducing operational complexity. These switches provide Gigabit Ethernet access and can be used at the edge of a network or to connect server clusters in small data centers.

High availability, simplified management, and comprehensive security control policies are among the key features that distinguish this series. This switch also supports dual modular power supplies.

Product Description: HPE 5130 24G PoE+ 4SFP+ 1-slot HI - switch - 24 ports - Managed - rack-mountable | Device Type: Switch - 24 ports - Managed - stackable | Enclosure Type: Rack-mountable 1U | Subtype: Gigabit Ethernet | Ports: 24 x 10/100/1000 (PoE+) + 4 x 10 Gigabit SFP+ | Power Over Ethernet (PoE): PoE+ | PoE Budget: 740 W | Performance: Throughput: up to 154.8 Mpps
Routing/switching capacity: 208 Gbps | Capacity: Simultaneous VLANs: 4094 IPv4 routing table entries: 32768 IPv6 routing table entries: 16384 | Jumbo Frame Support: 9KB | Routing Protocol: RIP-

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

1, RIP-2, IGMPv2, IGMP, PIM-SM, IGMPv3, MSDP, MLD | Remote Management Protocol: SNMP 1, RMON 1, RMON 2, RMON 3, RMON 9, Telnet, SNMP 3, SNMP 2c, HTTPS, TFTP, SSH-2, CLI, SCP | Features: Flow control, DHCP support, ARP support, VLAN support, auto-uplink (auto MDI/MDI-X), Syslog support, WRR queuing, IPv6 support, sFlow, STP support, RSTP support, VRRP support, MSTP support, PAgP support, ACL support, QoS, CAR, DHCP server, DLDP support, ECMP, STP Root Guard, IPv4 support, LLDP support, Smart Link Pass-Through, dynamic ARP protection, DHCP protection, port isolation, non blocking ports, SP, GARP, IRF technology, OpenFlow support, IP source guard | Compliant Standards: IEEE 802.3, IEEE 802.3u, IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3x, IEEE 802.1w, IEEE 802.1x, IEEE 802.3ae, IEEE 802.1s, IEEE 802.1ad, IEEE 802.3ah, IEEE 802.1ab (LLDP), IEEE 802.1ak, IEEE 802.3az | Power: AC 120/230 V (50/60 Hz) - power supply not installed | Power Redundancy: Optional | Dimensions (WxDxH): 43.99 cm x 46 cm x 4.37 cm | Weight: 12.5 kg

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950