



HPE 5510 48G PoE+ 4SFP+ HI Swch



Model: JH148A

Manufacturer: HEWLETT PACKARD ENTERPRISE

EAN: 888793785720

Product Code: 203025

R173,515

The HPE FlexNetwork 5510 HI Switch Series comprises Gigabit Ethernet switches that deliver outstanding resiliency, security, and multiservice support capabilities at the edge layer of data center, large campus, and metro Ethernet networks. The switches can also be used in the core layer of SMB networks. With Intelligent Resilient Fabric (IRF) support, the HPE FlexNetwork 5510 HI Series Switch can deliver high levels of resiliency and manageability. Designed with four fixed 10GbE ports and supports additional modular uplinks, these switches can provide up to six 10GbE uplink ports. With complete IPv4/IPv6, OpenFlow, and MPLS/VPLS features, the series provides investment protection with an easy transition from IPv4 to IPv6 networks.

Product Description: HPE 5510 48G PoE+ 4SFP+ HI 1-slot Switch - switch - 48 ports - Managed - rack-mountable | Device Type: Switch - 48 ports - L3 - Managed - stackable | Enclosure Type: Rack-mountable 1U | Subtype: Gigabit Ethernet | Ports: 48 x 10/100/1000 (PoE+) + 4 x 10 Gigabit SFP+ | Power Over Ethernet (PoE): PoE+ | PoE Budget: 1440 W | Performance: Routing/switching capacity: 336 Gbps Throughput: 250 Mpps | Capacity: IPv4 routing table entries: 32768 IPv6 routing table entries: 16384 | MAC Address Table Size: 32K entries | Jumbo Frame Support: Yes | Routing Protocol: OSPF, RIP, IS-IS, BGP, VRRP, PIM-SM, static IP routing, PIM-DM, OSPF for IPv6, OSPFv3, PIM-SSM,

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

ECMP, RIPng, IS-ISv6, MPLS, Bidirectional Forwarding Detection (BFD) | Remote Management Protocol: SNMP 1, SNMP, RMON, Telnet, SNMP 3, SNMP 2c, HTTP, SSH, SSH-2, CLI | Features: Flow control, Layer 3 switching, DHCP support, ARP support, MPLS support, auto-uplink (auto MDI/MDI-X), WRR queuing, IPv6 support, CBWFQ, WFQ, WRED, sFlow, STP support, RSTP support, VRRP support, MSTP support, DHCP snooping, QoS, RADIUS support, RRPP, ECMP, BFD, STP Root Guard, IPv4 support, DWRR, SP, 802.1x authentication, ToS, MACsec support, SDWRR, VPLS | Compliant Standards: IEEE 802.3, IEEE 802.3u, IEEE 802.3i, IEEE 802.3z, IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3af, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.3ae, IEEE 802.3ac, IEEE 802.1s, IEEE 802.1ad, IEEE 802.1v, IEEE 802.1ab (LLDP), IEEE 802.1ak, IEEE 802.3at, IEEE 802.3az | Power: AC 120/230 V - power supply not installed | Power Redundancy: Optional | Dimensions (WxDxH): 44 cm x 36 cm x 4.37 cm | Weight: 7.5 kg

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950