



HPE Aruba 2930F 48G 4SFP+ Swch Aruba 2930F 48G 4SFP+ Swch EU en

Model: JL254A#ABB

Manufacturer: HEWLETT PACKARD ENTERPRISE

EAN: 190017005263

Product Code: 203032

R134,625

The Aruba 2930F Switch series is designed for customer creating digital workplaces that are optimized for mobile users with an integrated wired and wireless approach. These basic Layer 3 access switches are easy to deploy and manage with advanced security and network management tools like Aruba ClearPass Policy Manager and Aruba AirWave and are ideal for enterprise edge, SMB and branch offices.

A powerful Aruba ProVision ASIC delivers performance and value supporting the latest SDN applications with future proof programmability. It supports 10GbE uplinks, PoE+, robust QoS, and RIP routing.

Product Description: HPE Aruba 2930F 48G 4SFP+ - switch - 48 ports - Managed - rack-mountable |

Device Type: Switch - 48 ports - L3 - Managed - stackable | Enclosure Type: Rack-mountable 1U |

Subtype: Gigabit Ethernet | Ports: 48 x 10/100/1000 + 4 x 1 Gigabit / 10 Gigabit SFP+ (uplink) |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Performance: Throughput: 112 Mpps Switching capacity: 176 Gbps Latency (1 Gbps): 3.8 μ s Latency (10 Gbps): 1.6 μ s | Capacity: Jumbo frame size: 9220 IPv4 routing table entries: 10000 IPv6 routing table entries: 5000 | MAC Address Table Size: 32K entries | Routing Protocol: OSPF, RIP, RIP-1, RIP-2, BGP, IGMPv2, IGMP, OSPFv2, static IP routing, IGMPv3, OSPFv3, static IPv4 routing, static IPv6 routing, RIPvng, MLD, CIDR | Remote Management Protocol: SNMP 1, SNMP 2, RMON 1, SNMP, Telnet, SNMP 3, SNMP 2c, SSH, SSH-2, CLI, XRMON | Features: Flow control, full duplex capability, DHCP support, BOOTP support, ARP support, VLAN support, IGMP snooping, Syslog support, DiffServ support, IPv6 support, STP support, sFlow, STP support, MSTP support, ACL support, QoS, Jumbo Frames support, DHCP server, STP Root Guard, UDLD, LLDP support, LACP, MIB, MAC address lockout, dynamic ARP protection, DHCP protection, GVRP, MVRP, NDP, CoS, ToS, OpenFlow support, CPU protection, ICMP, ICMP IRDP, VXLAN, MIB II | Compliant Standards: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.3af, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.1s, IEEE 802.1ad, IEEE 802.1v, IEEE 802.1ab (LLDP), IEEE 802.3az, IEEE 802.1AX | Power: AC 120/230 V | Dimensions (WxDxH): 44.25 cm x 24.63 cm x 4.39 cm | Weight: 3.1 kg | Localisation: English / Europe | Manufacturer Warranty: Limited lifetime warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950