



HPE Aruba 2930F 48G PoE+ 4SFP Swch Aruba 2930F 48G PoE+ 4SFP Swch EU en

Model: JL262A#ABB

Manufacturer: HEWLETT PACKARD ENTERPRISE

EAN: 190017005768

Product Code: 203038

R132,833

The Aruba 2930F switch series is designed for customers creating digital workplaces that are optimized for mobile users with an integrated wired and wireless approach. These basic Layer 3 access switches are easy to deploy and manage with advanced security and network management tools like Aruba ClearPass Policy Manager and Aruba AirWave. The 2930F supports 10GbE uplinks, PoE+, robust QoS, RIP routing, and IPv6 with no software licensing required. The Aruba 2930F switch series provides a convenient and cost-effective access switch solution that can be quickly set up.

Product Description: HPE Aruba 2930F 48G PoE+ 4SFP - switch - 48 ports - Managed - rack-mountable | Device Type: Switch - 48 ports - L3 - Managed - stackable | Enclosure Type: Rack-mountable 1U | Subtype: Gigabit Ethernet | Ports: 48 x 10/100/1000 (PoE+) + 4 x Gigabit SFP (uplink) | Power Over Ethernet (PoE): PoE+ | PoE Budget: 370 W | Performance: Throughput: 77.4

Mpps Switching capacity: 104 Gbps Latency (1 Gbps): 3.8 µs | Capacity: Jumbo frame size: 9220 IPv4

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

routing table entries: 10000 IPv6 routing table entries: 5000 | MAC Address Table Size: 32K entries | Routing Protocol: OSPF, RIP, RIP-1, RIP-2, IGMPv2, IGMP, OSPFv2, static IP routing, IGMPv3, OSPFv3, static IPv4 routing, static IPv6 routing, RIPng, MLD, CIDR | Remote Management Protocol: SNMP 1, SNMP 2, RMON 1, SNMP, Telnet, SNMP 3, SNMP 2c, SSH, SSH-2, CLI, XRMON | Features: Flow control, full duplex capability, DHCP support, BOOTP support, ARP support, VLAN support, IGMP snooping, Syslog support, DiffServ support, IPv6 support, SNTP support, sFlow, STP support, MSTP support, TFTP support, ACL support, QoS, Jumbo Frames support, DHCP server, MLD snooping, STP Root Guard, UDLD, LLDP support, DHCP relay, LACP, MIB, MAC address lockout, dynamic ARP protection, DHCP protection, GVRP, MVRP, NDP, CoS, SNMP support, ToS, OpenFlow support, CPU protection, ICMP, ICMP IRDP, VXLAN, MIB II | Compliant Standards: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.3af, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.1s, IEEE 802.1v, IEEE 802.1ab (LLDP), IEEE 802.3at, IEEE 802.3az, IEEE 802.1AX | Power: AC 120/230 V (50/60 Hz) | Dimensions (WxDxH): 44.25 cm x 30.42 cm x 4.39 cm | Weight: 4.46 kg | Localisation: English / Europe | Manufacturer Warranty: Limited lifetime warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950