



HPE 1950 12XGT 4SFP+ Switch HPE 1950 12XGT 4SFP+ Switch EU en



Model: JH295A#ABB

Manufacturer: HEWLETT PACKARD ENTERPRISE

EAN: 889296308607

Product Code: 203041

R54,191

The HPE OfficeConnect 1950 Switch Series has an intuitive Web-based interface for simple customization of network operation. It supports true-stacking, the aggregation switch supporting up to two devices, while the access switches allowing up to four devices, to be logically administered as a single entity, simplifying administration while supporting greater network redundancy. Models support both rack mounting and desktop operation. These switches have IPv4 and IPv6 operation, with Layer 2 switching as well as Layer 3 static routing. Other features include: link aggregation to boost link performance; VLANs, Access Control Lists, and 802.1X network login for enhanced security; and three versions of Spanning Tree Protocol (STP) for added network resiliency.

Product Description: HPE OfficeConnect 1950 12XGT 4SFP+ - switch - 12 ports - rack-mountable | Device Type: Switch - 12 ports | Enclosure Type: Rack-mountable 1U | Subtype: 10 Gigabit Ethernet | Ports: 12 x 10GBase-T + 4 x 1 Gigabit / 10 Gigabit SFP+ | Performance: Routing/switching capacity: 320 Gbps Throughput (64-byte packet size): 238 Mpps Latency (100 Mbps): 5 µs Latency (1000Base-

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

T): 5 μ s | Capacity: IPv4 routing table entries: 512 IPv6 routing table entries: 256 | MAC Address Table Size: 16384 entries | Jumbo Frame Support: 10KB | Remote Management Protocol: SNMP, RMON, HTTPS, CLI | Features: Flow control, full duplex capability, auto-negotiation, auto-uplink (auto MDI/MDI-X), half duplex mode, full duplex mode, QoS, 2MB packet buffer, DSCP support | Compliant Standards: IEEE 802.3, IEEE 802.3i, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3x, IEEE 802.3az | Power: AC 120/230 V (50/60 Hz) | Dimensions (WxDxH): 44 cm x 16 cm x 4.4 cm | Weight: 3.66 kg | Localisation: English / Europe | Manufacturer Warranty: Limited lifetime warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950