

HPE Aruba 3810M 48GPoE+4SFP+1050W Swch



Model: JL429A

Manufacturer: HEWLETT PACKARD ENTERPRISE

EAN: 190017142289

Product Code: 203046

R215,950

Powerful Aruba Advanced Layer 3 switch series with backplane stacking, low latency and resiliency for a better mobile-first campus network experience. Based on a powerful ProVision ASIC and ready for high-speed APs with HPE Smart Rate multi-gigabit Ethernet, the 3810 access solution is ideal for enterprises, SMBs, and branch office networks.

Product Description: HPE Aruba 3810M 48G PoE+ 4SFP+ 1050W - switch - 48 ports - Managed - rack-mountable | Device Type: Switch - 48 ports - L3 - Managed - stackable | Enclosure Type: Rack-mountable 1U | Subtype: Gigabit Ethernet | Ports: 48 x 10/100/1000 (PoE+) | Power Over Ethernet (PoE): PoE+ | Performance: Latency (1000Base-T): 2.8 µs Latency (10 Gbps): 1.8 µs Latency (40 Gbps): 1.5 µs Throughput (64-byte packet size): up to 190.5 Mpps Routing/switching capacity: 320 Gbps Switching fabric bandwidth: 338 Gbps | Capacity: IPv4 routing table entries: 10000 IPv6 routing table entries: 5000 | MAC Address Table Size: 64K entries | Jumbo Frame Support: Yes | Routing Protocol: OSPF, RIP, RIP-1, RIP-2, BGP, VRRP, OSPFv2, OSPFv3, static IPv4 routing, static IPv6 routing, RIPng, MLD, Bidirectional Forwarding Detection (BFD) | Remote Management Protocol: SNMP 1,

RMON 1, RMON 2, RMON 3, RMON 9, RMON, Telnet, SNMP 3, SNMP 2c, HTTP, SSH, SSH-2, CLI,

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

XRMON | Features: ARP support, STP support, PVST, ACL support, QoS, DLDP support, UDLD, MIB, GVRP, MVRP, CoS, sFlow v5, ToS, OpenFlow support, ICMP | Compliant Standards: IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3af, IEEE 802.3ad (LACP), IEEE 802.1x, IEEE 802.1s, IEEE 802.1v, IEEE 802.11n, IEEE 802.1ab (LLDP), IEEE 802.3at | Power: DC 54 V | Power Redundancy: Yes | Environmental Standards: ENERGY STAR Qualified | Dimensions (WxDxH): 44.25 cm x 43.13 cm x 4.39 cm | Weight: 6.18 kg

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950