



HPE Aruba 2930M 24G 1- slot Switch



Model: JL319A

Manufacturer: HEWLETT PACKARD ENTERPRISE

EAN: 190017071190

Product Code: 203047

R84,348

The Aruba 2930M Switch series is designed for customers creating digital workplaces that are optimized for mobile users with an integrated wired and wireless approach. These Layer 3 access switches are easy to deploy and manage with advanced security and network management tools like Aruba ClearPass Policy Manager and Aruba AirWave. With support from cloud-based Aruba Central, you can quickly set up remote offices with little or no IT support. A powerful Aruba ProVision ASIC delivers performance and value with support of the SDN apps with future proof programmability for tomorrow's applications. High performance modular stacking for up to 10 switches provides simplicity, scalability with a pay as you grow approach.

Product Description: HPE Aruba 2930M 24G 1-Slot - switch - 24 ports - Managed - rack-mountable |
Device Type: Switch - 24 ports - L3 - Managed - stackable | Enclosure Type: Rack-mountable 1U |
Subtype: Gigabit Ethernet | Ports: 20 x 10/100/1000 + 4 x combo Gigabit SFP | Performance:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Throughput: 95.2 Mpps Switching capacity: 128 Gbps Latency (1 Gbps): 3.1 μ s Latency (10 Gbps): 3.4 μ s Latency (10 Mbps): 98.5 μ s Latency (100 Mbps): 11.8 μ s | Capacity: Jumbo frame size: 9220 IPv4 routing table entries: 2000 IPv6 routing table entries: 1000 | MAC Address Table Size: 32768 entries | Routing Protocol: OSPF, RIP, RIP-1, RIP-2, IGMPv2, IGMP, OSPFv2, static IP routing, IGMPv3, OSPFv3, static IPv4 routing, static IPv6 routing, ECMP, RIPng, MLD, CIDR | Remote Management Protocol: SNMP 1, SNMP 2, RMON 1, SNMP, Telnet, SNMP 3, SNMP 2c, HTTP, SSH, SSH-2, CLI, XRMON | Features: Flow control, full duplex capability, DHCP support, BOOTP support, ARP support, VLAN support, IGMP snooping, Syslog support, DiffServ support, IPv6 support, SNTP support, sFlow, STP support, MSTP support, ACL support, QoS, Jumbo Frames support, DHCP server, MLD snooping, STP Root Guard, UDLD, LLDP support, LACP, MIB, MAC address lockout, dynamic ARP protection, DHCP protection, GVRP, MVRP, NDP, CoS, ToS, OpenFlow support, CPU protection, ICMP, ICMP IRDP, VXLAN, MIB II, LLDP-MED, STP BPDU Guard | Compliant Standards: IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3af, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.1s, IEEE 802.1v, IEEE 802.3az, IEEE 802.1AX, IEEE 802.3bz | Power: AC 120/230 V (50/60 Hz) - power supply not installed | Dimensions (WxDxH): 44.25 cm x 32.43 cm x 4.39 cm | Weight: 4.45 kg | Manufacturer Warranty: Limited lifetime warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950