



HPE SN2410M 25GbE 24SFP28 4QSFP28 Power to Connector Airflow Switch



Model: Q6M27A

Manufacturer: HEWLETT PACKARD ENTERPRISE

EAN: 190017199979

Product Code: 203056

R485,938

How can you provide fast, reliable, and cost-effective connectivity in the data center with predictable performance? HPE StoreFabric SN2410M switches are ideal for modern server and storage networks. They are an ideal top-of-rack solution with 10 and 25GbE or 100GbE systems with wire-speed Layer 2 and 3 features delivers predictable performance and zero packet loss at line-rate across all ports and packet sizes. Optimized for storage and efficient design provide enterprise-level performance with attractive economics and outstanding ROI. Networks built on the HPE SN2410M are fast, reliable, and scalable while also being affordable and easy to manage. They support all types of primary and secondary storage, providing consistently fair, fast, low-latency connectivity even under heavy workloads or a mix of different port speeds. This makes them ideal for storage, hyper converged, financial services, and media and entertainment deployments.

Product Description: HPE StoreFabric SN2410M 25GbE 24SFP28 4QSFP28 - switch - 24 ports - Managed - rack-mountable | Device Type: Switch - 24 ports - L3 - Managed | Enclosure Type: Rack-

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

mountable 1U | Subtype: 25 Gigabit Ethernet | Ports: 24 x 25 Gigabit SFP28 + 4 x 100 Gigabit QSFP28 | Performance: Switching capacity: 4 Tbps Processing rate: 5.95 Bpps Cut-through latency: 300 ns | Remote Management Protocol: SNMP, Telnet, SSH, CLI | Features: IGMP snooping, port mirroring, store and forward, IPv6 support, RSTP support, VRRP support, MSTP support, DCBX support, ACL support, QoS, BFD, IPv4 support, LLDP support, DHCP relay, sFlow v5, 802.1x authentication, 16MB packet buffer, OpenFlow support, Protocol-based VLANs support, Storm Control, RoCE, RED, ECN, PFC, VXLAN, MLAG, OSPF, Root Guard, Loop Guard, Voice VLAN, ToR, STP BPDU Guard, BPDU Filter, PIM, hot swap fan tray | Compliant Standards: X.509 | Power: AC 120/230 V (50/60 Hz) | Power Redundancy: Yes | Dimensions (WxDxH): 43.6 cm x 43.8 cm x 4.39 cm | Weight: 8.52 kg | Manufacturer Warranty: 3-year warranty | Designed For: Apollo 4200 Gen10 192TB Qumulo Hybrid Node, 4200 Gen10 336TB Archive Node with 25Gb NIC for Qumulo, 4200 Gen10 Qumulo Archive Node, 4200 Gen10 Qumulo Hybrid Node, 4200 Qumulo Archive Node, 4200 Qumulo Hybrid Node, 4200 Qumulo Node

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950