



HPE Aruba 8320 48 10/6 40 X472 5 2 Bdl Aruba 8320 48 10/6 40 X472 5 2 Bdl EU en



Model: JL479A#ABB

Manufacturer: HEWLETT PACKARD ENTERPRISE

EAN: 190017195490

Product Code: 203057

R656,328

The 8320 provides advanced line rate 10GbE/40GbE in a compact 1U form factor. The 8320 is based on the ArubaOS-CX, a modern software system for the enterprise core that automates and simplifies many critical and complex network tasks, delivers enhanced fault tolerance and facilitates zero-service disruption during planned or unplanned control-plane events. The Network Analytics Engine framework is made up of a time series database and associated REST APIs.

Product Description: HPE Aruba 8320 - switch - 48 ports - Managed - rack-mountable - TAA Compliant - with 2 x Aruba X371 400W AC Power Supply, 5 x Aruba X721 Front-to-Back Fan, Aruba X472 2-post Rack Kit | Device Type: Switch - 48 ports - L3 - Managed - with 2 x Aruba X371 400W AC Power Supply, 5 x Aruba X721 Front-to-Back Fan, Aruba X472 2-post Rack Kit | Enclosure Type: Rack-mountable 1U | Subtype: 10 Gigabit Ethernet | Ports: 48 x 10 Gigabit SFP+ + 6 x 40 Gigabit QSFP+ |

Performance: Switching capacity: 2.5 Tbps Forwarding performance: 1.905 Mpps | Capacity: Virtual

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

interfaces (VLANs) per port for 802.1q: 4096 | Jumbo Frame Support: 9KB | Routing Protocol: OSPF, IGMPv2, IGMP, VRRP, IGMPv3, GRE, static IPv6 routing, ECMP | Remote Management Protocol: SNMP, RMON, SNMP 3, SNMP 2c, TFTP, SFTP | Features: VPN support, IPv6 support, sFlow, STP support, RSTP support, MSTP support, ACL support, QoS, UDLD, Rapid PVST+, IPv4 support, LACP, redundant hot swappable fans, packet storm protection, SP, Loopback, BPDU, MLAG, PIM | Compliant Standards: IEEE 802.3z, IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.3ae, IEEE 802.1s, IEEE 802.1ad, IEEE 802.1t, IEEE 802.1ae, IEEE 802.1ab (LLDP), IEEE 802.1ak, IEEE 802.3ba, IEEE 802.1AX | Power: AC 120/230 V (50/60 Hz) | Power Redundancy: Yes | Dimensions (WxDxH): 44.2 cm x 50.55 cm x 4.32 cm | Weight: 9.4 kg | Localisation: English / Europe | TAA Compliant: Yes | Manufacturer Warranty: 5-year warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950