



HPE Aruba 2930F Switch 12G PoE+ 2G/2SFP+ Europe - English localization

Model: JL693A#ABB

Manufacturer: HEWLETT PACKARD ENTERPRISE

EAN: 190017368214

Product Code: 203076

R56,707

The Aruba 2930F Switch Series is designed for customers creating smart digital workplaces that are optimized for mobile users with an integrated wired and wireless approach. These convenient Layer 3 network switches include built-in uplinks and PoE power, and are simple to deploy and manage with advanced security and network management tools like Aruba ClearPass Policy Manager, Aruba AirWave and cloud-based Aruba Central.

Product Description: HPE Aruba 2930F 12G PoE+ 2G/2SFP+ - switch - 12 ports - Managed - rack-mountable | Device Type: Switch - 12 ports - L3 - Managed - stackable | Enclosure Type: Rack-mountable 1U | Subtype: Gigabit Ethernet | Ports: 12 x 10/100/1000 (PoE+) + 2 x 1 Gigabit / 10 Gigabit SFP+ (uplink) + 2 x 10/100/1000 | Power Over Ethernet (PoE): PoE+ | PoE Budget: 139 W | Performance: Throughput: 41.7 Mpps Switching capacity: 68 Gbps Latency (1 Gbps): 3.8 µs Latency (10 Gbps): 1.6 µs | Capacity: Jumbo frame size: 9220 IPv4 routing table entries: 2000 IPv6 routing

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

table entries: 1000 | MAC Address Table Size: 32K entries | Routing Protocol: OSPF, RIP, RIP-1, RIP-2, IGMPv2, IGMP, OSPFv2, static IP routing, IGMPv3, OSPFv3, static IPv4 routing, static IPv6 routing, RIPng, MLD, CIDR | Remote Management Protocol: SNMP 1, SNMP 2, RMON 1, SNMP, Telnet, SNMP 3, SSH, SSH-2, CLI, XRMON | Features: Flow control, full duplex capability, DHCP support, BOOTP support, ARP support, VLAN support, IGMP snooping, Syslog support, DiffServ support, IPv6 support, SNTP support, sFlow, STP support, MSTP support, TFTP support, ACL support, QoS, Jumbo Frames support, DHCP server, MLD snooping, STP Root Guard, UDLD, LLDP support, DHCP relay, LACP, MIB, MAC address lockout, dynamic ARP protection, DHCP protection, GVRP, MVRP, NDP, CoS, SNMP support, ToS, OpenFlow support, CPU protection, ICMP, ICMP IRDP, VXLAN, MIB II | Compliant Standards: IEEE 802.3, IEEE 802.3u, IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3af, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.1s, IEEE 802.1v, IEEE 802.1ab (LLDP), IEEE 802.3at, IEEE 802.3az, IEEE 802.1AX | Power: AC 120/230 V (50/60 Hz) | Dimensions (WxDxH): 25.4 cm x 25.4 cm x 4.39 cm | Weight: 2.2 kg | Localisation: English / Europe | Manufacturer Warranty: Limited lifetime warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950