TRENDNET 6-Port Industrial Gigabit L2 Managed DIN-Rail Switch

Model: TI-G642I

Manufacturer: TRENDNET

EAN: 710931161540

Product Code: 203087

R7,250

TRENDnet's Industrial Gigabit L2 Managed DIN-Rail Switch series offers advanced layer 2 managed features with enhanced traffic controls to meet the evolving demands of today's SMB networks. Each industrial layer 2 managed switch is equipped with an IP30 rated metal enclosure, designed to withstand a high degree of vibration and shock, while operating within a wide temperature range of -40° - 75°C (-40° - 167°F) for industrial environments. The industrial layer 2 managed switch models feature copper Gigabit ports for high-speed device connections, and SFP slots that support both 100Base-FX and 1000Base-FX modules for long distance fiber networking applications. These industrial layer 2 managed DIN-Rail switches provide an intuitive web-based management interface. Each TRENDnet industrial layer 2 managed switch supports advanced traffic management controls, troubleshooting, and SNMP monitoring. Advanced managed switch features include LACP to group ports together to increase bandwidth between switches, VLANs for segmenting and isolating virtual LAN groups, QoS for traffic prioritization, port bandwidth controls, and SNMP monitoring making each

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

TRENDnet industrial layer 2 managed switch a powerful solution for SMB networks.

Product Description: TRENDnet TI-G642I - switch - 6 ports - Managed - TAA Compliant | Device Type: Switch - 6 ports - Managed | Subtype: Gigabit Ethernet | Ports: 4 x 10/100/1000 + 2 x Gigabit SFP | Performance: Switching fabric bandwidth: 12 Gbps Forwarding performance (64-byte packet size): 18.9 Mpps | MAC Address Table Size: 8K entries | Jumbo Frame Support: 10KB | Routing Protocol: IGMPv2, IGMP, IGMPv3 | Remote Management Protocol: SNMP 1, RMON 1, RMON 2, RMON 3, RMON 9, SNMP 3, SNMP 2c, HTTP, SSH-2, CLI | Features: Auto-negotiation, Syslog support, port mirroring, store and forward, half duplex mode, full duplex mode, DDMI, STP support, RSTP support, DHCP snooping, DHCP server, reset button, bandwidth control, fanless, LLDP support, DHCP relay, CoS, 8KV ESD Protector, metal housing, DSCP support, queue scheduling support | Compliant Standards: IEEE 802.3, IEEE 802.3u, IEEE 802.3z, IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.1ab (LLDP), IEEE 802.3az, IEEE 802.1AX | Power: DC 20 - 60 V - power adapter not included | Power Redundancy: Yes | Dimensions (WxDxH): 5 cm x 12 cm x 16 cm | Weight: 720 g | TAA Compliant: Yes | Manufacturer Warranty: Limited lifetime warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950