TRENDNET 5-Port Industrial Fast Ethernet PoE+ DIN-Rail Switch

Model: TI-PE50

Manufacturer: TRENDNET

EAN: 710931161601

Product Code: 203090

R3,523

TRENDnet's Industrial Fast Ethernet PoE+ DIN-Rail Switches feature a rugged IP30 rated metal enclosure. These industrial unmanaged PoE+ switches are designed to withstand a high degree of vibration and shock, while operating in both high and low temperatures for industrial environments within -40° - 75°C (-40° - 167°F). Redundant power inputs with overload current protection on each industrial unmanaged PoE+ switch minimizes network downtime. Installers and integrators can save on equipment costs and reduce installation time with TRENDnet's Industrial Fast Ethernet Switches by delivering up to 30 W per port of PoE power and data over existing Ethernet cables. With PoE technology, users only need one set of cables to deliver both data and power from the industrial unmanaged PoE+ switch. With these industrial unmanaged PoE+ switches, easily network PoE devices such as high-power wireless access points, PTZ and other advanced IP cameras, VoIP phone systems, IPTV decoders, access controls, and more.

Product Description: TRENDnet TI-PE50 - switch - 5 ports - unmanaged - TAA Compliant | Device

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

Type: Switch - 5 ports - unmanaged | Subtype: Fast Ethernet | Ports: 4 x 10/100 (PoE+) + 1 x 10/100 | Power Over Ethernet (PoE): PoE+ | PoE Budget: 90 W | Performance: Switching fabric bandwidth: 1 Gbps Forwarding performance (64-byte packet size): 0.744 Mpps | MAC Address Table Size: 1K entries | Features: Auto-negotiation, store and forward, half duplex mode, full duplex mode, 56KB packet buffer, 6KV ESD Protector | Compliant Standards: IEEE 802.3, IEEE 802.3u, IEEE 802.3af, IEEE 802.3x, IEEE 802.3at | Power: DC 48 - 56 V - power adapter not included | Dimensions (WxDxH): 8.2 cm x 10.3 cm x 3.1 cm | Weight: 160 g | TAA Compliant: Yes | Manufacturer Warranty: Limited lifetime warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950