TP-Link 24-Port 10/100Mbps + 2-Port Gigabit Unmanaged PoE+ Switch

Model: TL-SL1226P

Manufacturer: TP-LINK

EAN: 1210002617185

Product Code: 203097

R4,986

Professional High Power 24-Port PoE+ Switch

Plug and Play, with PoE Transmission for Surveillance up to 250 m

- 250 W PoE Budget
- Transmission Distance up to 250 m
- One-Click Priority Mode
- One-Click Traffic Separation
- Ultra HD Video
- Plug and Play

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Dedicated 24-Port PoE+ Switch for Wide Range of Applications with 250 W PoE Budget

Compliance with the 802.3af/at PoE+ standard supports up to 30 W on each PoE port. The total 250 W PoE power budget for the 24× PoE ports makes it has wide range of applications, such as surveillance, offices, dormitories, and small businesses. It is fully compatible with IP cameras, access points, IP phones, computers, printers, and etc.

Dedicated Design for IP Surveillance—Up to 250 m Transmission

With extend mode, the PoE transmission distance reaches up to 250 m — perfect for IP Camera deployment in large areas.

Dedicated Design for IP Surveillance — Higher Performance and Security

Priority Video Quality Guaranteed

Quality of sensitive applications like video monitoring in critical business areas is guaranteed by offering higher priority options for ports 1–8 when one-touch Priority Mode is on.

One-Click Traffic Separation for Ports 1-24

With one click, Isolation Mode easily divides traffic for ports 1–24 to avoid snooping and tampering. This enables the switch to isolate broadcast storm, improving LAN security and data transmission.

Smooth HD Video Monitoring

2× gigabit RJ45 ports and 2× combo gigabit SFP ports ensure smooth streaming even when 24× HD IP cameras work simultaneously.

Intelligent Power Management to Prevent Power Overload

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

When your total power consumption exceeds 250 W, Intelligent Power Management automatically cuts lower priority ports’ power to ensure high-priority ports’ power supply. This protects the device from power overload operation. It also automatically detects the required PoE power for your device and protects your non-PoE equipment from being damaged.

Wide Operating Temperature with Good Heat Dissipation

Durable metal casing and professional heat dissipation design ensure the wide operating temperature (0–50℃) with reliability.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950