



HPE Aruba IOn 1930 48G 4SFP+ Switch



Model: JL685A

Manufacturer: HEWLETT PACKARD ENTERPRISE

EAN: 190017356112

Product Code: 203104

R15,060

Discover the HPE Networking Instant On 1930 48G 4SFP/SFP+ Switch, a high-performance networking solution designed to meet the demands of modern businesses. With 48 RJ-45 ports and 4 SFP+ ports, this switch offers extensive connectivity options for both Gigabit and 10Gbit LAN environments. It supports advanced Layer 2+ switching features such as VLAN support, Quality of Service (QoS), and Link Aggregation Control Protocol (LACP), enabling efficient network management and bandwidth utilization.

The switch is engineered for security, featuring RADIUS authentication and SSL encryption to protect network communications. Its robust design ensures reliability, with a mean time between failures (MTBF) of 114 years, ensuring a stable and dependable network infrastructure. Whether you're upgrading an existing network or building a new one, the HPE Networking Instant On 1930 48G 4SFP/SFP+ Switch is a smart investment for businesses seeking performance, security, and reliability.

Product Description: HPE Networking Instant On 1930 48G 4SFP/SFP+ Switch - switch - 48 ports - Managed - rack-mountable | Device Type: Switch - 48 ports - L2+ - Managed | Enclosure Type: Rack-mountable 1U | Subtype: 10 Gigabit Ethernet | Ports: 48 x 10/100/1000 + 4 x 1 Gigabit / 10 Gigabit

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

SFP+ | Performance: Throughput: 130.95 Mpps Switching capacity: 176 Gbps Latency (1 Gbps): 2.2 μ s Latency (10 Gbps): 1.2 μ s | Capacity: Routing table entries (static): 32 | MAC Address Table Size: 16K entries | Jumbo Frame Support: 9216 bytes | Routing Protocol: IGMPv2, IGMP, static IPv4 routing, MSTP, RSTP, STP | Remote Management Protocol: SNMP, RMON, SNMP 3, SNMP 2c, HTTP, HTTPS, TFTP, SCP, DHCP, IPv4, IPv6 | Features: Flow control, DHCP support, ARP support, trunking, VLAN support, auto-uplink (auto MDI/MDI-X), IGMP snooping, port mirroring, manageable, IPv6 support, half duplex mode, full duplex mode, STP support, RSTP support, MSTP support, ACL support, QoS, Jumbo Frames support, TPM, IPv4 support, LACP support, LLDP support, LACP, CoS, SNMP support, 1.5MB packet buffer, BPDU, LLDP-MED, EEE | Compliant Standards: IEEE 802.3, IEEE 802.3u, IEEE 802.3z, IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.1s, IEEE 802.1ab (LLDP), IEEE 802.3az | Power: AC 120/230 V (50/60 Hz) | Dimensions (WxDxH): 44.25 cm x 28.24 cm x 4.39 cm | Weight: 3.13 kg | Manufacturer Warranty: Limited lifetime warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950