



HPE Aruba Instant On 1930 Switch 8G 2SFP Europe - English localization



Model: JL680A#ABB

Manufacturer: HEWLETT PACKARD ENTERPRISE

EAN: 190017355030

Product Code: 203105

R4,729

The HPE Networking Instant On 1930 8G 2SFP Switch is a powerful and versatile networking solution designed to meet the demands of modern businesses. With robust security features, including RADIUS authentication and SSL encryption, it ensures secure access and data transmission across the network. The switch has a high-performance architecture with a 20 Gbps switching capacity and support for up to 14.88 Mpps throughput, capable of handling high-volume traffic with minimal latency.

Its comprehensive set of networking features, such as Layer 3 switching, VLAN support, and Quality of Service (QoS), allows for the creation of sophisticated network architectures and efficient traffic management. Additionally, the switch offers flexible connectivity options with its 8 RJ-45 ports and 2 Gigabit SFP ports, accommodating both copper and fiber connections. Designed for durability and reliability, it complies with a wide range of safety and environmental standards, ensuring a long-lasting networking solution for any business environment.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Product Description: HPE Networking Instant On 1930 8G 2SFP Switch - switch - 10 ports - Managed | Device Type: Switch - 10 ports - L3 - Managed | Subtype: Gigabit Ethernet | Ports: 8 x 10/100/1000 + 2 x Gigabit SFP | Performance: Switching capacity: 20 Gbps Throughput: 14.88 Mpps Latency (100 Mbps): 5.2 µs Latency (1 Gbps): 3 µs | Capacity: Link aggregation ports: 8 IPv4 routes (static): 32 VLANs supported: 256 Access Control Entries (ACEs) per ACL: 480 Packet buffer size: 1.5 MB | MAC Address Table Size: 8000 entries | Jumbo Frame Support: 9216 bytes | Routing Protocol: Static IP routing | Remote Management Protocol: SNMP 1, RMON, SNMP 3, SNMP 2c, HTTP, HTTPS, TFTP, RADIUS | Features: Flow control, DHCP support, ARP support, VLAN support, auto-uplink (auto MDI/MDI-X), IGMP snooping, IPv6 support, half duplex mode, full duplex mode, STP support, MSTP support, ACL support, QoS, TPM, LLDP support, LACP, Energy Efficient Ethernet, CoS, BPDU Filter | Compliant Standards: IEEE 802.3, IEEE 802.3u, IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3af, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.1s, IEEE 802.1ab (LLDP), IEEE 802.3at, IEEE 802.3az | Power: AC 120/230 V (50/60 Hz) | Dimensions (WxDxH): 25.4 cm x 15.95 cm x 4.39 cm | Weight: 820 g | Localisation: English / Europe | Manufacturer Warranty: Limited lifetime warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950