



HPE Aruba Instant On 1930 Switch 8G 2SFP 124W Europe - English localization



Model: JL681A#ABB

Manufacturer: HEWLETT PACKARD ENTERPRISE

EAN: 190017355238

Product Code: 203106

R7,002

The HPE Networking Instant On 1930 8G Class4 PoE 2SFP 124W Switch is designed to meet the demands of modern businesses, offering a blend of performance, security, and manageability. With a PoE budget of 124 W, it powers connected devices efficiently, while its security features like RADIUS authentication and SSL encryption ensure a secure network environment. The switch boasts a high throughput of 14.88 Mpps and a switching capacity of 20 Gbps, facilitating swift data processing and transfer. Advanced networking capabilities such as Layer 2+ switching, VLAN support, and Quality of Service (QoS) enable effective traffic prioritization and network segmentation, enhancing overall network performance. Additionally, its comprehensive management options via HTTP, HTTPS, SNMP, and RMON allow for seamless integration and easy management within any network infrastructure. This switch is an ideal solution for businesses looking to optimize their network's performance and security.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Product Description: HPE Networking Instant On 1930 8G Class4 PoE 2SFP 124W Switch - switch - 10 ports - Managed - rack-mountable | Device Type: Switch - 10 ports - L3 - Managed | Enclosure Type: Rack-mountable 1U | Subtype: Gigabit Ethernet | Ports: 8 x 10/100/1000 (PoE) + 2 x Gigabit SFP | Power Over Ethernet (PoE): PoE | PoE Budget: 124 W | Performance: Switching capacity: 20 Gbps Throughput: 14.88 Mpps Latency (100 Mbps): 5.2 µs Latency (1 Gbps): 3 µs | Capacity: Link aggregation ports: 8 IPv4 routes (static): 32 VLANs supported: 256 Access Control Entries (ACEs) per ACL: 480 Packet buffer size: 1.5 MB | MAC Address Table Size: 8000 entries | Jumbo Frame Support: 9216 bytes | Routing Protocol: Static IP routing | Remote Management Protocol: SNMP 1, RMON, SNMP 3, SNMP 2c, HTTP, HTTPS, TFTP, RADIUS | Features: Flow control, DHCP support, ARP support, VLAN support, auto-uplink (auto MDI/MDI-X), IGMP snooping, IPv6 support, half duplex mode, full duplex mode, STP support, MSTP support, ACL support, QoS, TPM, LLDP support, LACP, Energy Efficient Ethernet, CoS, BPDU Filter, PoE Class 4 | Compliant Standards: IEEE 802.3, IEEE 802.3u, IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3af, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.1s, IEEE 802.1ab (LLDP), IEEE 802.3at, IEEE 802.3az, IEEE 802.2af | Power: AC 120/230 V (50/60 Hz) | Dimensions (WxDxH): 25.4 cm x 25.4 cm x 4.39 cm | Weight: 1.16 kg | Localisation: English / Europe | Manufacturer Warranty: Limited lifetime warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950