



HPE Aruba Instant On 1930 Switch 24G 4SFP+ Europe - English localization



Model: JL682A#ABB

Manufacturer: HEWLETT PACKARD ENTERPRISE

EAN: 190017355450

Product Code: 203107

R9,050

The HPE Networking Instant On 1930 24G 4SFP/SFP+ Switch is designed to meet the needs of growing businesses requiring a secure and manageable networking solution. This switch offers a robust set of features including 24 gigabit RJ-45 ports and 4 SFP+ ports for high-speed connections, supporting a variety of network configurations. With a switching capacity of 128 Gbps and support for up to 95.23 million packets per second, it ensures efficient traffic management and high-speed data transmission.

Advanced security features such as SSL encryption and RADIUS authentication protect sensitive data and control network access, making it an ideal choice for businesses concerned with data security. Additionally, the switch's support for up to 256 VLANs allows for extensive network segmentation, enabling better traffic management and increased security. Its energy-efficient design not only

reduces operational costs but also contributes to a greener environment. With its comprehensive set

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

of features and reliable performance, the HPE Networking Instant On 1930 24G 4SFP/SFP+ Switch is a valuable asset for any business looking to enhance its network infrastructure.

Product Description: HPE Networking Instant On 1930 24G 4SFP/SFP+ Switch - switch - 28 ports - Managed - rack-mountable | Device Type: Switch - 28 ports - L3 - Managed | Enclosure Type: Rack-mountable 1U | Subtype: Gigabit Ethernet | Ports: 24 x 10/100/1000 + 4 x 1 Gigabit / 10 Gigabit SFP+ | Performance: Switching capacity: 128 Gbps Throughput: 95.23 Mpps Latency (1 Gbps): 2.4 µs Latency (10 Gbps): 1.3 µs | Capacity: Link aggregation ports: 8 IPv4 routes (static): 32 VLANs supported: 256 Access Control Entries (ACEs) per ACL: 480 Packet buffer size: 1.5 MB | MAC Address Table Size: 16000 entries | Jumbo Frame Support: 9216 bytes | Routing Protocol: Static IP routing | Remote Management Protocol: SNMP 1, RMON, SNMP 3, SNMP 2c, HTTP, HTTPS, TFTP, RADIUS | Features: Flow control, DHCP support, ARP support, VLAN support, auto-uplink (auto MDI/MDI-X), IGMP snooping, IPv6 support, half duplex mode, full duplex mode, STP support, MSTP support, ACL support, QoS, TPM, LLDP support, LACP, Energy Efficient Ethernet, CoS, BPDU Filter | Compliant Standards: IEEE 802.3, IEEE 802.3u, IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3af, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.1s, IEEE 802.1ab (LLDP), IEEE 802.3at, IEEE 802.3az | Power: AC 120/230 V (50/60 Hz) | Dimensions (WxDxH): 44.25 cm x 22.15 cm x 4.39 cm | Weight: 2.41 kg | Localisation: English / Europe | Manufacturer Warranty: Limited lifetime warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950