

HPE Aruba Instant On 1930 Switch 24G 4SFP+ 370W Europe - English localization



Model: JL684A#ABB

Manufacturer: HEWLETT PACKARD ENTERPRISE

EAN: 190017355894

Product Code: 203109

R16,874

The HPE Networking Instant On 1930 24G Class4 PoE 4SFP/SFP+ 370W Switch is a high-performance, rack-mountable network solution designed to meet the demands of modern businesses. With 24 PoE ports and 4 SFP+ ports, it offers extensive connectivity options for devices requiring high-speed network access and power over Ethernet. This switch has a robust 128 Gbps switching capacity and a throughput of 95.23 Mpps, ensuring efficient data flow across the network. Advanced security features such as Access Control List (ACL) support, SSL encryption, and RADIUS authentication provide a secure networking environment, safeguarding against unauthorized access and cyber threats. Additionally, the switch is manageable via multiple protocols, including HTTP, HTTPS, SNMP, and RADIUS, offering flexibility in network management and monitoring. Its durable design, evidenced by a 71-year mean time between failures (MTBF) and compliance with stringent

environmental standards, ensures long-term reliability and performance. This makes the HPE

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Networking Instant On 1930 switch an ideal choice for businesses looking for a secure, manageable, and high-capacity networking solution.

Product Description: HPE Networking Instant On 1930 24G Class4 PoE 4SFP/SFP+ 370W Switch - switch - 28 ports - Managed - rack-mountable | Device Type: Switch - 28 ports - L3 - Managed | Enclosure Type: Rack-mountable 1U | Subtype: Gigabit Ethernet | Ports: 24 x 10/100/1000 (PoE) + 4 x 1 Gigabit / 10 Gigabit SFP+ | Power Over Ethernet (PoE): PoE | PoE Budget: 370 W | Performance: Switching capacity: 128 Gbps Throughput: 95.23 Mpps Latency (1 Gbps): 2.4 µs Latency (10 Gbps): 1.3 µs | Capacity: Link aggregation ports: 8 IPv4 routes (static): 32 VLANs supported: 256 Access Control Entries (ACEs) per ACL: 480 Packet buffer size: 1.5 MB | MAC Address Table Size: 16000 entries | Jumbo Frame Support: 9216 bytes | Routing Protocol: Static IP routing | Remote Management Protocol: SNMP 1, RMON, SNMP 3, SNMP 2c, HTTP, HTTPS, TFTP, RADIUS | Features: Flow control, DHCP support, ARP support, VLAN support, auto-uplink (auto MDI/MDI-X), IGMP snooping, IPv6 support, half duplex mode, full duplex mode, STP support, MSTP support, ACL support, QoS, TPM, LLDP support, LACP, Energy Efficient Ethernet, CoS, BPDU Filter, PoE Class 4 | Compliant Standards: IEEE 802.3, IEEE 802.3u, IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3af, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.1s, IEEE 802.1ab (LLDP), IEEE 802.3at, IEEE 802.3az, IEEE 802.2af | Power: AC 120/230 V (50/60 Hz) | Dimensions (WxDxH): 44.25 cm x 26.47 cm x 4.39 cm | Weight: 3.67 kg | Localisation: English / Europe | Manufacturer Warranty: Limited lifetime warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950