HPE Aruba Instant On 1930 Switch 48G 4SFP+ 370W Europe - English localization

Model: JL686A#ABB

Manufacturer: HEWLETT PACKARD ENTERPRISE

EAN: 190017356334

Product Code: 203111

R24,514

The HPE Networking Instant On 1930 48G Class4 PoE 4SFP/SFP+ 370W Switch is a high-performance, rack-mountable network solution designed to meet the demands of modern businesses. With 48 PoE ports and 4 SFP+ ports, it offers extensive connectivity options for various devices, making it ideal for environments requiring high-speed networking and device power via Ethernet. This switch boasts a robust 176 Gbps switching capacity and supports up to 256 VLANs, ensuring efficient data traffic handling and network segmentation. Security is a priority, with features like Access Control Lists (ACLs), SSL encryption, and RADIUS authentication providing comprehensive protection for sensitive data. Additionally, its ENERGY STAR Ethernet and a generous 370 W PoE budget help minimize operational costs by optimizing power usage. Manageable via multiple protocols, including HTTP, HTTPS, SNMP, and RMON, it offers flexible and straightforward network management. Whether for a small business or a large enterprise, the HPE Networking Instant On 1930 switch is engineered to

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

provide reliable, secure, and efficient network performance.

Product Description: HPE Networking Instant On 1930 48G Class4 PoE 4SFP/SFP+ 370W Switch - switch - 52 ports - Managed - rack-mountable | Device Type: Switch - 52 ports - L2+ - Managed | Enclosure Type: Rack-mountable 1U | Subtype: Gigabit Ethernet | Ports: 48 x 10/100/1000 (PoE) + 4 x 1 Gigabit / 10 Gigabit SFP+ | Power Over Ethernet (PoE): PoE | PoE Budget: 370 W | Performance: Switching capacity: 176 Gbps Throughput: 130.95 Mpps Latency (1 Gbps): 2.2 µs Latency (10 Gbps): 1.2 µs | Capacity: Link aggregation ports: 8 IPv4 routes (static): 32 VLANs supported: 256 Access Control Entries (ACEs) per ACL: 480 Packet buffer size: 1.5 MB | MAC Address Table Size: 16000 entries | Jumbo Frame Support: 9216 bytes | Routing Protocol: Static IP routing | Remote Management Protocol: SNMP 1, RMON, SNMP 3, SNMP 2c, HTTP, HTTPS, TFTP, RADIUS | Features: Flow control, DHCP support, ARP support, VLAN support, auto-uplink (auto MDI/MDI-X), IGMP snooping, IPv6 support, half duplex mode, full duplex mode, STP support, MSTP support, ACL support, QoS, TPM, LLDP support, LACP, Energy Efficient Ethernet, CoS, BPDU Filter, PoE Class 4 | Compliant Standards: IEEE 802.3, IEEE 802.3u, IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3af, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.1s, IEEE 802.1ab (LLDP), IEEE 802.3at, IEEE 802.3az, IEEE 802.2af | Power: AC 120/230 V (50/60 Hz) | Dimensions (WxDxH): 44.25 cm x 32.26 cm x 4.39 cm | Weight: 4.52 kg | Localisation: English / Europe | Manufacturer Warranty: Limited lifetime warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950