



HPE Aruba 6100 Switch 12G CL4 2SFP+ 139W Europe - English localization



Model: JL679A#ABB

Manufacturer: HEWLETT PACKARD ENTERPRISE

EAN: 190017348964

Product Code: 203147

R37,978

The Aruba CX 6100 switch series is a modern family of entry-level access switches ideal for branch offices, mid-market enterprise, and SMB networks. Designed for reliable, simple, and secure access, the Aruba CX 6100 switch provides a convenient wired access solution for enterprise networks supporting IoT, mobile, and cloud applications. Prepare your network for unpredictable demands with a powerful Aruba ASIC architecture and programmable AOS-CX operating system used across the Aruba CX portfolio to deliver a more consistent, more efficient operator experience. This switch series has convenient built-in high-speed uplinks to support IoT devices such as security cameras and wireless APs. A compact and fanless model is ideal for use in quiet work spaces.

Product Description: HPE Aruba 6100 12G Class4 PoE 2G/2SFP+ 139W Switch - switch - 16 ports - Managed - rack-mountable | Device Type: Switch - 16 ports - Managed - stackable | Enclosure Type: Rack-mountable 1U | Subtype: 10 Gigabit Ethernet | Ports: 12 x 10/100/1000 (PoE+) + 2 x 1 Gigabit / 10 Gigabit SFP+ + 2 x 1000Base-T | Power Over Ethernet (PoE): PoE+ | PoE Budget: 139 W |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Performance: Switching capacity: 68 Gbps Throughput: 45.1 Mpps Latency (1 Gbps): 2.3 μ s Latency (10 Gbps): 2.6 μ s | Capacity: Switched virtual interfaces (SVIs): 16 ARP entries: 1024 IPv4 routes (Unicast): 512 IPv6 routes (Unicast): 512 IGMP groups: 512 MLD groups: 512 IPv4 ACL entries (ingress): 256 IPv6 ACL entries (ingress): 128 MAC ACL entries (ingress): 256 | MAC Address Table Size: 8192 entries | Routing Protocol: IGMPv2, IGMPv3 | Features: DNS client, VLAN support, MSTP support, RSTP, LACP support, Energy Efficient Ethernet, flow control, UDP, TFTP support, ARP support, DHCP client, ICMP, SNMP support, BOOTP support, DiffServ support, EntityMIB, IPv6 addressing, IPv6 support, LLDP support, LLDP-MED, MIB, MLD snooping, NDP, NAC, port based access control, sFlow, SNMP support, fanless | Compliant Standards: IEEE 802.1D, IEEE 802.1p, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1w, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad (LACP), IEEE 802.3at, IEEE 802.3az, IEEE 802.3x | Power: AC 230V (50/60 Hz) | Dimensions (WxDxH): 25.4 cm x 25.5 cm x 4.39 cm | Weight: 2.78 kg | Localisation: English / Europe | Manufacturer Warranty: Limited lifetime warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950