



CISCO Business Switching CBS220 Smart 24-port Gigabit 4x1G SFP uplink

Model: CBS220-24T-4G-EU

Manufacturer: CISCO

EAN: 889728344807

Product Code: 203168

R5,481

The Cisco Business CBS220-24T-4G switch is simple and affordable smart switch for business-class network. CBS220 series bridge the gap between the affordability of an unmanaged device and the ease-of-use of smart switches. With their intuitive dashboard and mobile app support, these switches deliver a solid business network.

Product Description: Cisco Business 220 Series CBS220-24T-4G - switch - 28 ports - smart - rack-mountable | Device Type: Switch - 28 ports - smart | Enclosure Type: Rack-mountable | Subtype: Gigabit Ethernet | Ports: 24 x 10/100/1000 + 4 x Gigabit SFP (uplink) | Performance: Forwarding performance (64-byte packet size): 41.66 Mpps Switching capacity: 56 Gbps | Capacity: MSTP instances: 16 VLANs supported: 256 ACL rules: 512 Buffer capacity (MB): 4.1 | MAC Address Table Size: 8192 entries | Jumbo Frame Support: 9216 bytes | Routing Protocol: STP, RSTP, MSTP, IGMP, IGMPv2, IGMPv3, MLD, MLDv2 | Remote Management Protocol: RSTP, ICMP, RADIUS, TACACS+, SSH, SCP, SSH-2, HTTPS, HTTP, Telnet, CLI, SNMP 1, SNMP 2c, SNMP 3, RMON, TFTP, DHCP | Features:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

QoS, 802.1x authentication, ACL support, BPDU Guard, DoS attack prevention, Energy Efficient Ethernet, MAC address filtering, LACP support, VLAN support, VLAN management, Guest VLAN, auto voice VLAN, GVRP, HOL Blocking Prevention, loopback detection, Auto MDIX, DSCP support, UDP, TCP support, Port Security, Broadcast Storm Control, Multicast Storm Control, Unknown Storm Control, STP loop guard, WRR, ToS, DiffServ support, IGMP snooping, NDP, DAD, Telnet server, DHCP client, CDP, LLDP support, MIB, port mirroring, dual firmware images, BOOTP support, Cable Diagnostics Function, Syslog support, LLDP-MED, fanless | Compliant Standards: IEEE 802.1x, IEEE 802.3az, IEEE 802.1D, IEEE 802.1w, IEEE 802.1s, IEEE 802.3ad (LACP), IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3z, IEEE 802.1ab (LLDP), IEEE 802.3x | Power: AC 100-240 V (50/60 Hz) | Dimensions (WxDxH): 44 cm x 20.3 cm x 4.4 cm | Weight: 2.75 kg | Localisation: European Economic Area, Switzerland, Turkey, Russia, Ukraine, Israel, United Arab Emirates, Egypt, South Africa, Indonesia, Philippines, Vietnam, Thailand, Korea | Manufacturer Warranty: 3-year warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950