



HPE FlexNetwork 5140 EI Switch 24G PoE+ 370W 4 SFP+ Ports including PSU

Model: JL827A

Manufacturer: HEWLETT PACKARD ENTERPRISE

EAN: 190017500164

Product Code: 203171

R117,960

The HPE FlexNetwork 5140 EI Switch Series delivers scalability, high availability, and low TCO at the access layer of medium and large enterprise campus networks. The series offers enterprise-class QoS and security, Hewlett Packard Enterprise Intelligent Resilient Fabric (IRF) stacking, static layer 3 routing and RIP, convenient fixed 10GbE uplink ports, PoE+, ACLs, and IPv6, and delivers energy savings with Energy Efficient Ethernet.

The HPE FlexNetwork 5140 EI Switch Series also includes Smart Management Center (SmartMC), an embedded network management tool that can be leveraged at no additional cost by small and medium networks for centralized management and operations. The series can also be managed with HPE Intelligent Management Center (IMC) for a single view of your entire network.

Product Description: HPE FlexNetwork 5140 24G PoE+ 4SFP+ EI - switch - 28 ports - smart - rack-mountable | Device Type: Switch - 28 ports - L3 - smart | Enclosure Type: Rack-mountable 1U |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Subtype: Gigabit Ethernet | Ports: 24 x 10/100/1000 (PoE+) + 4 x combo 10/100/1000Base-T (PoE+) / 100/1000Base-X SFP + 4 x 10 Gigabit Ethernet / 1 Gigabit Ethernet SFP+ | Power Over Ethernet (PoE): PoE+ | PoE Budget: 370 W | Performance: Latency (1000 Mbps): 5 μ s Latency (10 Gbps): 3 μ s Throughput: 96 Mpps Routing/switching capacity: 128 Gbps | Capacity: IPv4 routing table entries: 512 IPv6 routing table entries: 256 VLAN IDs: 4094 | MAC Address Table Size: 16384 entries | Jumbo Frame Support: 9216 bytes | Routing Protocol: OSPF, RIP-1, RIP-2, IGMP, OSPFv2, IGMPv3, OSPFv3, static IPv4 routing, static IPv6 routing, CIDR | Remote Management Protocol: SNMP 1, RMON 1, RMON 2, RMON 3, RMON 9, Telnet, SNMP 3, SNMP 2c, HTTPS, TFTP, CLI, NTP, ICMP, RADIUS | Features: Flow control, BOOTP support, ARP support, load balancing, VLAN support, auto-uplink (auto MDI/MDI-X), IGMP snooping, DiffServ support, High Availability, half duplex mode, full duplex mode, sFlow, STP support, RSTP support, VRRP support, MSTP support, ACL support, QoS, CAR, DHCP server, MLD snooping, DLDLP support, STP Root Guard, DHCP relay, LACP, Port Security, Energy Efficient Ethernet, dynamic ARP protection, DHCP protection, MVRP, SPQ, port isolation, GARP, OpenFlow support, IP source guard, ICMP Router Discovery Protocol (IRDP), Link Aggregation, VLAN Double Tagging (Q-in-Q), LLDP-MED, Smart Link, Guest VLAN, Ethernet OAM, proxy ARP, WRR, IRF Technology, BPDU protection, UDP support, MRP | Compliant Standards: IEEE 802.3, IEEE 802.3u, IEEE 802.3i, IEEE 802.3z, IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3af, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.3ae, IEEE 802.3ac, IEEE 802.1s, IEEE 802.1ad, IEEE 802.3ah, ANSI/TIA-1057, IEEE 802.1ab (LLDP), IEEE 802.1ak, IEEE 802.3at, IEEE 802.3az, IEEE 802.1AX, IEEE 802.1r | Power: AC 100-240 V (50/60 Hz) | Dimensions (WxDxH): 44 cm x 26 cm x 4.36 cm | Weight: 8 kg | Manufacturer Warranty: Limited lifetime warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950