

HPE Aruba IOn 1960 12XT 4XF Switch



Model: JL805A

Manufacturer: HEWLETT PACKARD ENTERPRISE

EAN: 190017521770

Product Code: 203175

R54,664

The HPE Networking Instant On 1960 12XGT 4SFP+ Switch is designed to meet the demands of modern businesses, offering robust performance, comprehensive connectivity, and advanced security features. With a throughput of 238 Mpps and a switching capacity of 320 Gbps, it ensures efficient handling of network traffic, suitable for environments with high data demands. The switch provides versatile connectivity options with its 12 RJ-45 connectors for 10/100/1000 Base-T and 4 SFP+ connectors for 10 Gigabit Ethernet, accommodating a wide range of network architectures. Advanced security features such as Access Control List (ACL) support, Trusted Platform Module (TPM), and RADIUS authentication protect against unauthorized access, ensuring a secure network environment. Additionally, the switch is manageable via HTTP, HTTPS, SNMP 1, SNMP 2c, and SNMP 3, allowing for easy configuration and monitoring of your network infrastructure. Built to last, with an MTBF of 88.8 years and compliance with multiple safety and environmental standards, the HPE Networking Instant On 1960 12XGT 4SFP+ Switch is a reliable and durable solution for your networking needs.

Product Description: HPE Networking Instant On 1960 12XGT 4SFP+ Switch - switch - 12 ports - Managed - rack-mountable | Device Type: Switch - 12 ports - Managed | Enclosure Type: Rack-

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

mountable 1U | Subtype: 10 Gigabit Ethernet | Ports: 12 x 100/1000/10000 + 4 x 10 Gigabit SFP+ | Performance: Throughput: 238 Mpps Switching capacity: 320 Gbps Latency (100 Mbps): 7.4 µs Latency (1 Gbps): 4.2 µs Latency (10 Gbps): 1.1 µs | Capacity: MAC address entries: 16000 IPv4 routes (static): 512 IPv6 routes (static): 512 | MAC Address Table Size: 16000 entries | Jumbo Frame Support: 9216 bytes | Routing Protocol: Static IP routing | Remote Management Protocol: RADIUS, SNMP 1, SNMP 2c, SNMP 3, HTTP, HTTPS | Features: IEEE 802.3ad (LACP), IEEE 802.1ab (LLDP), IEEE 802.1D, IEEE 802.1s, IEEE 802.1Q, IEEE 802.1p | Power: AC 100-240 V (50/60 Hz) | Dimensions (WxDxH): 44.25 cm x 35.05 cm x 4.395 cm | Weight: 4.3 kg | Pricing Type: BTO | Manufacturer Warranty: Limited lifetime warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950