



HPE Aruba Instant On 1960 24G 2XT 2XF PoE+ 370W Switch



Model: JL807A

Manufacturer: HEWLETT PACKARD ENTERPRISE

EAN: 190017521589

Product Code: 203176

R36,007

The HPE Networking Instant On 1960 24G 20p Class4 4p Class6 PoE 2XGT 2SFP+ 370W Switch is designed to meet the demands of modern businesses, offering a blend of performance, security, and flexibility. With its 24 gigabit ports, additional 10 gigabit SFP+ and RJ-45 ports, and a substantial PoE budget, this switch is capable of supporting a wide range of devices and applications. Advanced security features ensure your network is protected against threats, while compliance with numerous standards demonstrates its reliability and durability. Whether you're upgrading your existing infrastructure or building a new network, this switch provides the capabilities you need to support your business's growth.

Product Description: HPE Networking Instant On 1960 24G 20p Class4 4p Class6 PoE 2XGT 2SFP+ 370W Switch - switch - 24 ports - Managed - rack-mountable | Device Type: Switch - 24 ports - L3 Lite - Managed - stackable | Enclosure Type: Rack-mountable 1U | Subtype: Gigabit Ethernet | Ports: 24 x 10/100/1000 + 2 x 10 Gigabit SFP+ + 2 x 100/1000/10GBase-T | Power Over Ethernet (PoE):

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

PoE | PoE Budget: 370 W | Performance: Throughput: 95 Mpps Switching capacity: 128 Gbps Latency (100 Mbps): 4.4 µs Latency (1 Gbps): 2.2 µs Latency (10 Gbps): 1.1 µs | Capacity: MAC address entries: 16000 IPv4 routes (static): 32 IPv6 routes (static): 32 | MAC Address Table Size: 16000 entries | Jumbo Frame Support: 9216 bytes | Routing Protocol: Static IP routing | Remote Management Protocol: RADIUS, SNMP 1, SNMP 2c, SNMP 3, HTTP, HTTPS | Features: IEEE 802.3, ARP support, auto-uplink (auto MDI/MDI-X), DHCP support, TPM, VLAN support, auto voice VLAN, LLDP-MED, LACP, STP support, BPDU Filter, flow control, IPv6 support, auto-negotiation, ACL support, CoS, port mirroring, full duplex mode, half duplex mode | Compliant Standards: IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3ad (LACP), IEEE 802.1ab (LLDP), IEEE 802.1D, IEEE 802.1s, IEEE 802.1Q, IEEE 802.1p | Power: AC 100-240 V (50/60 Hz) | Dimensions (WxDxH): 44.25 cm x 35.05 cm x 4.395 cm | Weight: 4.7 kg | Pricing Type: BTO | Manufacturer Warranty: Limited lifetime warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950