



HPE SN3600B 32Gb 24/8 8- port 16Gb Short Wave SFP+ Fibre Channel Switch



Model: R4G55B

Manufacturer: HEWLETT PACKARD ENTERPRISE

EAN: 190017520483

Product Code: 203184

R322,239

Are you struggling to meet the I/O demands of hyperscale virtualization, cloud, or growing flash-based SANs? HPE B-series SN3600B Fiber Channel Switch provides Gen6 32 Gb Fiber Channel (FC) in an ultra-dense 1U format and is affordable for limited budgets. It can replace three generations of FC with its backward compatibility with 4, 8, and 16 Gb FC for your investment protection. Designed to build a flash-ready infrastructure, it specifically adapts to business application needs. Applications requiring more throughput and lower latency can take advantage of NVMe over FC ready support as well. SAN simplicity is achieved with a simple 3-step install process and SAN deployments with HPE 3PAR all-flash storage are automated using HPE Smart SAN for HPE 3PAR software. Data reliability is enhanced with forward error correction (FEC) by automatically detecting and recovering bit error along with HPE Power Pack+ software, which maintains efficient SAN-health.

Product Description: HPE SN3600B 32Gb 24/8 8-port 16Gb Short Wave SFP+ Fibre Channel Switch -

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

switch - 24 ports - Managed - rack-mountable | Device Type: Switch - 24 ports - Managed | Enclosure Type: Rack-mountable 1U | Subtype: Fibre Channel | Ports: 8 x 16Gb Fibre Channel SFP+ + 16 x 32Gb Fibre Channel SFP+ Ports on Demand | Performance: Port-to-port latency: 900 ns | Capacity: Maximum frame size: 2112 Frame buffers: 2000 | Remote Management Protocol: HTTP, SNMP 1, SNMP 3, HTTPS, CLI, LDAP, SSH, SSH-2, SFTP, SMI-S | Features: IPv6 support, RBAC, SCP, Trusted Switch, Secure RPC, Syslog support, IP address filtering | Power: AC 90-264 V (50/60 Hz) | Dimensions (WxDxH): 42.88 cm x 30.66 cm x 4.29 cm | Weight: 5.76 kg | Manufacturer Warranty: Limited lifetime warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950