



HPE Aruba Switch IOn 1830 24G 2SFP Europe - English



Model: JL812A#ABB

Manufacturer: HEWLETT PACKARD ENTERPRISE

EAN: 190017518893

Product Code: 203193

R7,337

The HPE Networking Instant On 1830 24G 2SFP Switch is a high-performance, rack-mountable switch designed for small to medium-sized businesses. With 24 10/100/1000 ports and 2 Gigabit SFP ports, it offers ample connectivity for a variety of networking needs. The switch is engineered to provide a secure and efficient networking environment, featuring advanced security protocols such as SSL encryption and a Trusted Platform Module (TPM) to protect against unauthorized access and network threats.

This switch also emphasizes energy efficiency with its Energy-Efficient Ethernet (EEE) support and fanless design, making it an environmentally friendly choice that operates quietly. Additionally, it is equipped with a powerful ARM processor and 512 MB of SDRAM, ensuring smooth data processing and reliable performance. Comprehensive network management is made easy with support for SNMP, HTTP, and HTTPS, allowing for efficient monitoring and maintenance. Whether upgrading an existing network or setting up a new one, the HPE Networking Instant On 1830 24G 2SFP Switch is a versatile and secure solution that meets the demands of modern businesses.

Product Description: HPE Networking Instant On 1830 24G 2SFP Switch - switch - 24 ports - smart -

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

rack-mountable | Device Type: Switch - 24 ports - smart | Enclosure Type: Rack-mountable 1U | Subtype: Gigabit Ethernet | Ports: 24 x 10/100/1000 + 2 x Gigabit SFP | Performance: Latency (100 Mbps): 5.2 μ s Latency (1 Gbps): 2.8 μ s Throughput: 38.68 Mpps Switching capacity: 52 Gbps | MAC Address Table Size: 16000 entries | Jumbo Frame Support: 9216 bytes | Routing Protocol: IGMP, IGMPv2 | Remote Management Protocol: HTTP, HTTPS, ICMP, SNMP 1, SNMP 2c, SCP, TFTP | Features: Auto-sensing per device, 1.5MB packet buffer, fanless, wall mountable, Cable Diagnostics Function, event log, Syslog support, dual image support, EEE, SCP, Global Storm Control, BPDU Filter, DoS protection, flow control, IGMP snooping, Link Aggregation, LLDP support, loop protection, port mirroring, STP support, TPM, VLAN support, Port Scheduling, auto-negotiation, auto-uplink (auto MDI/MDI-X), CoS, cloud managed, DHCP client, firmware upgradable, QoS, SNTP support | Compliant Standards: IEEE 802.1p, IEEE 802.1Q, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad (LACP), IEEE 802.3u, IEEE 802.3x, IEEE 802.3z, IEEE 802.1ab (LLDP), IEEE 802.1D, IEEE 802.1w, IEEE 802.3ac, IEEE 802.3af, IEEE 802.3az | Power: AC 100-240 V (50/60 Hz) | Dimensions (WxDxH): 44.3 cm x 21.59 cm x 4.39 cm | Weight: 2.49 kg | Localisation: English / Europe | Manufacturer Warranty: Limited lifetime warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950