HPE Aruba Switch IOn 1830 24G 2SFP 195W

Model: JL813A

Manufacturer: HEWLETT PACKARD ENTERPRISE

EAN: 190017523743

Product Code: 203194

R11,256

The HPE Networking Instant On 1830 24G 12p Class4 PoE 2SFP 195W Switch is designed to meet the demands of modern businesses, offering a blend of performance, security, and manageability. With 24 Gigabit Ethernet ports, including 12 with PoE+ capability, it provides the necessary infrastructure to support both current and emerging network devices. Security is a priority, with features like SSL encryption and DoS protection ensuring a secure network environment. The switch is also cloud-managed, offering flexibility and ease in network management from anywhere. Performance is ensured, with a 52 Gbps switching capacity and up to 38.68 Mpps throughput, ensuring smooth data flow even in high-demand scenarios. Additionally, its energy-efficient design not only reduces operational costs but also supports environmental sustainability initiatives. Ideal for businesses looking for a scalable, secure, and high-performing networking solution.

Product Description: HPE Networking Instant On 1830 24G 12p Class4 PoE 2SFP 195W Switch - switch - 24 ports - smart - rack-mountable | Device Type: Switch - 24 ports - smart | Enclosure Type: Rack-mountable 1U | Subtype: Gigabit Ethernet | Ports: 12 x 10/100/1000 + 12 x 10/100/1000 (PoE+) + 2 x Gigabit SFP | Power Over Ethernet (PoE): PoE+ | PoE Budget: 195 W | Performance: Latency (100 Mbps): 5.2 µs Latency (1 Gbps): 2.8 µs Throughput: 38.68 Mpps Switching capacity: 52

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Gbps | MAC Address Table Size: 16000 entries | Jumbo Frame Support: 9216 bytes | Routing Protocol: IGMP, IGMPv2 | Remote Management Protocol: HTTP, HTTPS, ICMP, SNMP 1, SNMP 2c, SCP, TFTP | Features: Auto-sensing per device, 1.5MB packet buffer, wall mountable, Cable Diagnostics Function, event log, Syslog support, dual image support, EEE, SCP, Global Storm Control, BPDU Filter, DoS protection, flow control, IGMP snooping, Link Aggregation, LLDP support, loop protection, port mirroring, STP support, TPM, VLAN support, Port Scheduling, auto-negotiation, auto-uplink (auto MDI/MDI-X), CoS, cloud managed, DHCP client, firmware upgradable, QoS, SNTP support | Compliant Standards: IEEE 802.1p, IEEE 802.1Q, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad (LACP), IEEE 802.3u, IEEE 802.3x, IEEE 802.3z, IEEE 802.1ab (LLDP), IEEE 802.1D, IEEE 802.1w, IEEE 802.3ac, IEEE 802.3af, IEEE 802.3az, IEEE 802.3at | Power: AC 100-240 V (50/60 Hz) | Dimensions (WxDxH): 44.3 cm x 25.3 cm x 4.39 cm | Weight: 3.47 kg | Manufacturer Warranty: Limited lifetime warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950