



HPE Aruba Switch IOn 1830 48G 4SFP



Model: JL814A

Manufacturer: HEWLETT PACKARD ENTERPRISE

EAN: 190017519784

Product Code: 203196

R13,444

The HPE Networking Instant On 1830 48G 4SFP Switch is a versatile and reliable solution for businesses seeking to enhance their network infrastructure. With 48 RJ-45 1000Base-T ports and 4 Gigabit SFP slots, it offers extensive connectivity options to meet various networking needs. This switch is engineered for performance, featuring a powerful ARM processor and 512 MB of SDRAM to ensure efficient data processing and network operation. Security is a priority, with SSL encryption and a Trusted Platform Module (TPM) safeguarding against unauthorized access and network threats. Additionally, the switch's support for Energy-Efficient Ethernet (EEE) and a low operational power consumption make it an eco-friendly choice for any organization. Comprehensive management capabilities through various protocols allow for easy monitoring and maintenance of the network, ensuring optimal performance and reliability. Whether for a small office or a large enterprise, the HPE Networking Instant On 1830 48G 4SFP Switch is designed to deliver secure, efficient, and manageable networking solutions.

Product Description: HPE Networking Instant On 1830 48G 4SFP Switch - switch - 48 ports - smart - rack-mountable | Device Type: Switch - 48 ports - smart | Enclosure Type: Rack-mountable 1U | Subtype: Gigabit Ethernet | Ports: 48 x 10/100/1000 + 4 x Gigabit SFP | Performance: Latency (100

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Mbps): 5.2 μ s Latency (1 Gbps): 2.8 μ s Throughput: 77.37 Mpps Switching capacity: 104 Gbps | MAC Address Table Size: 16000 entries | Jumbo Frame Support: 9216 bytes | Routing Protocol: IGMP, IGMPv2 | Remote Management Protocol: HTTP, HTTPS, ICMP, SNMP 1, SNMP 2c, SCP, TFTP | Features: Auto-sensing per device, 1.5MB packet buffer, wall mountable, Cable Diagnostics Function, event log, Syslog support, dual image support, EEE, SCP, Global Storm Control, BPDU Filter, DoS protection, flow control, IGMP snooping, Link Aggregation, LLDP support, loop protection, port mirroring, STP support, TPM, VLAN support, Port Scheduling, auto-negotiation, auto-uplink (auto MDI/MDI-X), CoS, cloud managed, DHCP client, firmware upgradable, QoS, SNTP support | Compliant Standards: IEEE 802.1p, IEEE 802.1Q, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad (LACP), IEEE 802.3u, IEEE 802.3x, IEEE 802.3z, IEEE 802.1ab (LLDP), IEEE 802.1D, IEEE 802.1w, IEEE 802.3ac, IEEE 802.3af, IEEE 802.3az | Power: AC 100-240 V (50/60 Hz) | Dimensions (WxDxH): 44.3 cm x 25.3 cm x 4.39 cm | Weight: 3.54 kg | Manufacturer Warranty: Limited lifetime warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950