



## **HPE FlexNetwork 5140 HI Switch 48G 4 SFP+ Ports 1 Slot without PSU**

Model: R9L62A

Manufacturer: HEWLETT PACKARD ENTERPRISE

EAN: 190017587875

Product Code: 203203

## **R172,737**

The HPE FlexNetwork 5140 HI switch is engineered to meet the demands of modern network environments, offering robust security, high performance, and comprehensive networking features. It provides advanced Layer 3 switching capabilities, ensuring efficient management of network traffic and supporting a wide range of protocols and standards for compatibility and integration ease. With a focus on security, it features multiple authentication methods to protect against unauthorized access. The switch's high throughput and low latency rates ensure that data flows smoothly across the network, making it suitable for data-intensive applications. Additionally, its energy-efficient design and flexible management options make it an ideal choice for businesses looking to optimize their network's performance and manageability while minimizing their environmental impact. Whether you're upgrading an existing network or building a new one, the HPE FlexNetwork 5140 HI offers the reliability, performance, and security you need to support your business operations.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Product Description: HPE FlexNetwork 5140 HI - switch - 1-slot - 48 ports - Managed - rack-mountable | Device Type: Switch - 48 ports - L3 - Managed | Enclosure Type: Side to back airflow rack-mountable 1U | Subtype: Gigabit Ethernet | Ports: 48 x 10/100/1000 + 4 x 10 Gigabit Ethernet / 1 Gigabit Ethernet SFP+ | Performance: Latency (1000 Mbps): 5 µs Latency (10 Gbps): 3 µs Throughput: 180 Mpps Routing/switching capacity: 336 Gbps | MAC Address Table Size: 32K entries | Jumbo Frame Support: 9KB | Routing Protocol: OSPF, RIP-1, RIP-2, IGMP, OSPFv2, OSPFv3, static IPv4 routing, static IPv6 routing, CIDR, VRRP, VRRPE | Remote Management Protocol: SNMP 1, RMON 1, RMON 2, RMON 3, RMON 9, Telnet, SNMP 3, SNMP 2c, HTTPS, TFTP, CLI, NTP, ICMP, RADIUS, SNMP 6, SSH-2 | Features: Flow control, BOOTP support, ARP support, load balancing, VLAN support, auto-uplink (auto MDI/MDI-X), IGMP snooping, High Availability, sFlow, STP support, RSTP support, MSTP support, ACL support, QoS, CAR, MLD snooping, DLDp support, STP Root Guard, DHCP relay, LACP, Port Security, Energy Efficient Ethernet, dynamic ARP protection, DHCP protection, MVRP, port isolation, OpenFlow support, IP source guard, ICMP IRDP, Link Aggregation, LLDP-MED, Smart Link, Guest VLAN, proxy ARP, WRR, IRF Technology, UDP support, MRP, EAD, STP BPDU port protection, DHCP server | Compliant Standards: IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.1ab (LLDP), IEEE 802.3i, IEEE 802.1Q, IEEE 802.1D, IEEE 802.1p, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.3ae, IEEE 802.3ac, IEEE 802.1s, IEEE 802.1ad, IEEE 802.3ah, ANSI/TIA-1057, IEEE 802.1ak, IEEE 802.3az, IEEE 802.1AX, IEEE 802.1r, IEEE 802.3z, IEEE 802.1v, IEEE 802.1ae | Dimensions (WxDxH): 44 cm x 36 cm x 4.36 cm | Weight: 6.7 kg | Manufacturer Warranty: Limited lifetime warranty

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](http://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950