



HPE Aruba Instant On 1430 5G Switch



Model: R8R44A

Manufacturer: HEWLETT PACKARD ENTERPRISE

EAN: 190017600987

Product Code: 203212

R1,659

The HPE Networking Instant On 1430 5G Switch offers a blend of performance, reliability, and flexibility, making it a suitable solution for small to medium-sized business networks. With a 10 Gbps switching capacity and 7.44 Mpps throughput, it ensures efficient data transfer and connectivity. Its fanless design allows for silent operation, making it suitable for any office environment. The switch is designed to operate reliably in a wide range of environmental conditions, ensuring consistent performance. Advanced features such as support for IEEE 802.3az, VoIP, and Spanning Tree Protocol enhance its networking capabilities, while compliance with a broad set of standards ensures compatibility with various devices and global regulatory requirements. Whether for upgrading an existing network or setting up a new one, the HPE Networking Instant On 1430 5G Switch is a robust and versatile choice.

Product Description: HPE Networking Instant On 1430 5G Switch - switch - 5 ports - unmanaged |
Device Type: Switch - 5 ports - unmanaged | Subtype: Gigabit Ethernet | Ports: 5 x 10/100/1000 |
Performance: Throughput: 7.44 Mpps Switching capacity: 10 Gbps Latency (100 Mbps): 3.81 µs
Latency (1 Gbps): 0.93 µs | Capacity: MAC address entries: 8192 | MAC Address Table Size: 8192
entries | Jumbo Frame Support: 9216 bytes | Features: 1MB packet buffer, fanless, wall mountable,

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

DSCP support, VoIP support, MDI/MDI-X switch, flow control, auto-sensing per device, STP support | Compliant Standards: IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3az, IEEE 802.3x, IEEE 802.3z, IEEE 802.3i | Power: AC 100-240 V (50/60 Hz) 1 A | Dimensions (WxDxH): 11.6 cm x 9.3 cm x 2.6 cm | Weight: 270 g | Pricing Type: BTO | Manufacturer Warranty: Limited lifetime warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950