HPE Aruba Instant On 1430 16G Class4 PoE 124W Switch

Model: R8R48A

Manufacturer: HEWLETT PACKARD ENTERPRISE

EAN: 190017602202

Product Code: 203215

R7,847

The HPE Networking Instant On 1430 16G Class4 PoE 124W Switch is a high-performance, reliable networking solution designed to meet the needs of small to medium-sized businesses. With its 124 W PoE budget, it can power multiple devices such as VoIP phones and wireless access points directly through the network cables, eliminating the need for additional power sources and reducing clutter. This switch also offers exceptional throughput of 23.8 Mpps and a switching capacity of 32 Gbps, ensuring smooth and efficient data transmission across the network. Its 16 Gigabit Ethernet ports provide ample connectivity for devices, making it an ideal choice for businesses looking to expand their network. Additionally, the switch's fanless design allows for silent operation, making it suitable for noise-sensitive environments. With its robust set of features and compliance with numerous standards, the HPE Networking Instant On 1430 16G Class4 PoE 124W Switch is a versatile and dependable choice for any growing business.

Product Description: HPE Networking Instant On 1430 16G Class4 PoE 124W Switch - switch - 16 ports - unmanaged - rack-mountable | Device Type: Switch - 16 ports - unmanaged | Enclosure Type: Rack-mountable 1U | Subtype: Gigabit Ethernet | Ports: 16 x 10/100/1000 (PoE Class 4) | Power Over

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Ethernet (PoE): PoE | PoE Budget: 124 W | Performance: Throughput: 23.8 Mpps Switching capacity: 32 Gbps Latency (100 Mbps): 2.7 µs Latency (1 Gbps): 1.8 µs | Capacity: MAC address entries: 8192 | MAC Address Table Size: 8192 entries | Jumbo Frame Support: 9216 bytes | Features: 2MB packet buffer, fanless, wall mountable, DSCP support, VoIP support, MDI/MDI-X switch, flow control, auto-sensing per device, STP support, EEE | Compliant Standards: IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3az, IEEE 802.3x, IEEE 802.3z, IEEE 802.3i | Power: AC 100-127/200-240 V (50/60 Hz) 1.7 A | Dimensions (WxDxH): 27.5 cm x 26 cm x 4.4 cm | Weight: 2.09 kg | Pricing Type: BTO | Manufacturer Warranty: Limited lifetime warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950